

EUROLITE LED CSL-50 Spotlight

High power 50 W spotlight with neutral white light

Art. No.: 41600490

GTIN: 4026397699692



Features:

- 1 LED 70 W COB (chip-on-board) neutral white (NW)
- The device is cooled by passive convection cooling
- Control via plug and play
- With a beam angle of 50°
- Good color rendering index (CRI)
- With mounting bracket
- For application areas such as: Trade fair and shop fitting; advertisement/Shop window; restaurants, bars and hotels
- Silent operation
- Application possibility: Suspended; on stand; wall mounting

Logistic

EAN / GTIN: 4026397699692

Weight: 2,25 kg

Length: 0.30 m

Width: 0.23 m

Height: 0.14 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	50 W
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug
Cable construction:	3 x 0.75 mm ² H05VV-F
Cable length:	Approx. 0.8 m
Lamp type:	LED lamp
LED type:	1 x 70 W COB (chip-on-board) neutral white (NW)

Cooling:	Passive convection cooling
Control:	Plug and play
Beam angle:	50°
Beam angle (1/2 peak):	50°
Beam angle (1/10 peak):	90°
Color temperature:	4190K
Color rendering index (CRI):	83 Ra
Illuminance in Lux (lx):	1m: 2787 lx, 3m: 366 lx, 6m: 108 lx
Luminous flux:	3462 lm
Housing color:	White matte
Attachment system:	Mounting bracket
Material:	Aluminum casting; metal
Dimensions:	Length: 21.0 cm Width: 20.5 cm Height: 22.0 cm
Weight:	2.00 kg
Noise classification:	Class 0 (no noise at all)
Energy efficiency class (A - G):	G
EPREL-Nr:	1023949
Diameter mounting holes:	2 x Ø4mm
Material:	Metal, 1 mm
Diameter mounting holes:	1 x Ø10mm; 1 x Ø8mm
Material:	Metal, 2 mm
Dimensions:	Width: 19.7 cm Depth: 2.5 cm Height: 14.5 cm
Diameter mounting holes:	1 x Ø10mm; 6 x Ø4mm
Material:	Metal, 2.5 mm
Dimensions:	Length: 10.5 cm Width: 2.8 cm

Scope of delivery:

1 x spotlight
 1 x barndoor
 1 x mounting bracket
 1 x holder
 1 x screw
 1 x nut
 1 x user manual