# EUROLITE LED CSL-200 Spotlight black

High power 200 W spotlight with cold white light

**Art. No.: 41600505**

GTIN: 4026397724936











## List price: 153.51 €

incl. 19% VAT.

### Features:

- 1 LED 200 W COB (chip-on-board) cold white (CW)
- The device is cooled by cooling fan
- Control via plug and play
- With a beam angle of 7°
- Very high color rendering index (CRI)
- With mounting bracket
- For application areas such as: Trade fair and shop fitting; video and photography
- Application possibility: Suspended; on stand

### Logistic

EAN / GTIN: 4026397724936
Weight: 3,45 kg
Length: 0.44 m
Width: 0.24 m
Heigth: 0.24 m

### Technical specifications:

| | |
|---|---|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 215 W |
| Protection class: | Protection class I |
| Power connection: | Mains input via P-Con (blue), mounting version |
| Power output: | 1 x P-Con (grey), mounting version |
| Fuse: | T 10 A fuse fix on board |
| Lamp type: | LED lamp |
| LED type: | 1 x 200 W COB (chip-on-board) cold white (CW) |
| Cooling: | Cooling fan |

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

| | |
|---|---|
| Control: | Plug and play |
| Beam angle: | 7° |
| Beam angle (1/2 peak): | 7° |
| Beam angle (1/10 peak): | 25° |
| Color temperature: | 7000K |
| Color rendering index (CRI): | 93 Ra |
| Illuminance in Lux (lx): | 1m: 54191 lx, 3m: 9540 lx, 6m: 2501 lx |
| Luminous flux: | 16000 lm |
| Housing color: | Black matte |
| Attachment system: | Mounting bracket |
| Material: | Metal; aluminum casting |
| Slot for spot length: | Ø 23 cm |
| Dimensions: | Length: 37.2 cm<br>Diameter: Ø 23.5 cm |
| Weight: | 3.00 kg |
| Noise classification: | Class 2 (slight noise) |
| Energy efficiency class (A - G): | G |
| EPREL-Nr: | 1765375 |
| Diameter mounting holes: | 2 x Ø10mm |
| Material: | Metal, 2.5 mm |

## Scope of delivery:

1 x device
1 x user manual
1 x power cord

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.