

EUROLITE LED KKL-40 Floodlight 3CT white

LED floodlight with 3 color temperatures and extension arm with screw clamp for fixation

Art. No.: 41600600

GTIN: 4026397757941



Features:

- Direct color temperature selection for 3 preset values
- Easy mounting via screw clamp
- Inclination angle of the LED head manually adjustable
- Frost filter
- With a beam angle of 120°
- For tabletops with up to 40 mm strength
- 162 LEDs 0.5 W SMD 3528 cold white (CW)
- 162 LEDs 0.5 W SMD 3528 warm white (WW)
- Mains input and output for power linking up to 8 units
- The device is cooled by passive convection cooling
- Available in various colors

Logistic

EAN / GTIN: 4026397757941
Weight: 1,50 kg
Length: 0.62 m
Width: 0.27 m
Heigh: 0.11 m

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	40 W
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug
Power output:	IEC connector (F) mounting version
Lamp type:	LED lamp
LED type:	162 x 0.5 W SMD 3528 cold white (CW)

	162 x 0.5 W SMD 3528 warm white (WW)
Equipment:	Frost filter
Cooling:	Passive convection cooling
Beam angle:	120°
Beam angle (1/2 peak):	120°
Beam angle (1/10 peak):	120°
Color temperature:	3000K; 4100K; 6700K
Clamp area:	5 - 40 mm
Material:	Metal
Dimensions:	Length: 58 cm Width: 26.5 cm Height: 20 cm
Weight:	1.33 kg
Energy efficiency class (A - G):	G

Scope of delivery:

- 1 x spotlight
- 1 x power cord
- 1 x user manual
- 1 x washer
- 1 x knurled screw