

EUROLITE LED Theatre COB 100 UV

LED theatre spot with ultra violet (UV) 100 W COB (chip-on-board) LED

Art. No.: 41602020

GTIN: 4026397702378



Features:

- With a beam angle of 40°
- Flicker-free
- With double bracket
- Mains input and output for power linking up to 8 units
- Control via DMX; stand-alone; master/slave function; sound to light via microphone; CRMX by LumenRadio via USB (optional); QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional)
- For application areas such as: Stage; clubs/dancing school; decoration; wedding/gala/events; mobile djs / entertainer; party room; restaurants, bars and hotels; theater
- Application possibility: Standing; suspended; on stand
- Can be operated in 1; 4 CH mode

Logistic

EAN / GTIN: 4026397702378

Weight: 3,10 kg

Length: 0.26 m

Width: 0.23 m

Height: 0.34 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	85 W
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (grey), mounting version
Fuse:	5 x 20 mm, T 1 A fuse replaceable
Lamp type:	LED lamp

LED type:	1 x 100 W COB (chip-on-board) ultra violet (UV)
Flash rate:	0 - 20 Hz
DMX channels:	1; 4
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	DMX; stand-alone; master/slave function; sound to light via microphone; CRMX by LumenRadio via USB (optional); QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional)
Fixtures available for:	Light´J; Light Captain; Colorchief
Projection:	Flicker-free
Beam angle:	40°
Beam angle (1/2 peak):	40°
Beam angle (1/10 peak):	70°
Illuminance in Lux (lx):	Ultra violet (UV) 1m: 38 lx, 3m: 6 lx, 6m: 2 lx
Wavelength:	Ultra violet (UV) 402 nm
Housing color:	Black
Attachment system:	Double bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Width: 24.3 cm Depth: 31.1 cm Height: 32.0 cm
Weight:	2.75 kg
Noise classification:	Class 2 (slight noise)
Photobiological safety:	Risk Group 0

Scope of delivery:

1 x spotlight
1 x power cord
1 x user manual