

## EUROLITE LED Theatre COB 200 WW/CW

LED theatre spot with 2in1 CW/WW W COB (chip-on-board) LED

Art. No.: 41602034

GTIN: 4026397686548



**List price: 415.31 €**

incl. 19% VAT.

### Features:

- With a beam angle of 17°
- Variable color temperature 2500 K - 5700 K
- Very high color rendering index (CRI)
- Very quiet working noise
- Flicker-free
- Control via stand-alone; IR remote control; DMX; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- 1 LED COB (chip-on-board) 2in1 CW/WW (homogenous color mix)
- Dimmer electronic
- Strobe effect
- Integrated show programs
- With double bracket
- Mains input and output for power linking up to 8 units
- For application areas such as: Stage; wedding/gala/events; Trade fair and shop fitting; theater; rental; video and photography
- Application possibility: Standing; suspended; on stand
- Can be operated in 2; 4; 5; 7 CH mode

### Logistic

EAN / GTIN: 4026397686548

Weight: 4,85 kg

Length: 0.45 m

Width: 0.31 m

Height: 0.28 m

### Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 150 W

Protection class: Protection class I

|                              |                                                                                                                                                                                                              |
|------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power connection:            | Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)                                                                                                                 |
| Power output:                | P-Con (grey), mounting version                                                                                                                                                                               |
| Lamp type:                   | LED lamp                                                                                                                                                                                                     |
| LED type:                    | 1 x COB (chip-on-board) 2in1 CW/WW (homogenous color mix)                                                                                                                                                    |
| Flash rate:                  | 0.5 - 24 Hz                                                                                                                                                                                                  |
| DMX channels:                | 2; 4; 5; 7                                                                                                                                                                                                   |
| DMX input:                   | 3-pin XLR (M) mounting version                                                                                                                                                                               |
| DMX output:                  | 3-pin XLR (F) mounting version                                                                                                                                                                               |
| Cooling:                     | Cooling fan                                                                                                                                                                                                  |
| Control:                     | Stand-alone; IR remote control; DMX; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) |
| Fixtures available for:      | Light´J; Light Captain; Colorchief                                                                                                                                                                           |
| Projection:                  | Flicker-free                                                                                                                                                                                                 |
| PWM frequency:               | 2900 Hz                                                                                                                                                                                                      |
| Beam angle:                  | 17°                                                                                                                                                                                                          |
| Beam angle (1/2 peak):       | 17°                                                                                                                                                                                                          |
| Beam angle (1/10 peak):      | 35°                                                                                                                                                                                                          |
| Color temperature:           | 2500K - 5700K adjustable                                                                                                                                                                                     |
| Color rendering index (CRI): | 98 Ra                                                                                                                                                                                                        |
| Housing color:               | Black matte                                                                                                                                                                                                  |
| Attachment system:           | Double bracket                                                                                                                                                                                               |
| Display type:                | LCD display                                                                                                                                                                                                  |
| Material:                    | Aluminum casting                                                                                                                                                                                             |
| Dimensions:                  | Width: 25.95 cm<br>Depth: 20.00 cm<br>Height: 37.65 cm                                                                                                                                                       |
| Weight:                      | 4.11 kg                                                                                                                                                                                                      |
| Noise classification:        | Class 1 (very slight noise, suitable for noise-sensitive environments)                                                                                                                                       |
| Photobiological safety:      | Risk Group 0                                                                                                                                                                                                 |
| Diameter mounting holes:     | 3 x Ø11mm                                                                                                                                                                                                    |
| Material:                    | Metal, 2.5 mm                                                                                                                                                                                                |
| Cable construction:          | 3 x 1.0 mm² H05VV-F                                                                                                                                                                                          |
| Cable length:                | Approx. 1.2 m                                                                                                                                                                                                |
| Battery:                     | 1 x button cell 3.0 V CR2025 lithium manganese built-in                                                                                                                                                      |

## Scope of delivery:

1 x device  
 1 x power cord  
 1 x remote control  
 1 x battery  
 1 x user manual