

EUROLITE LED Theatre COB 200 RGBAL

LED theatre spot with 5in1 RGBAL 200 W COB (chip-on-board) LED

Art. No.: 41602036

GTIN: 4026397752991



Description:

This spotlight offers the ideal compromise between professional design and affordability. It is equipped with a high-output LED whose color mixing is based not only on red, green, and blue, but also on amber and lime. This results in significantly improved orange and yellow tones, as well as very good white light with adjustable color temperature.

This makes the spotlight perfect for both colored and white light. The housing is made of robust metal. At the same time, the fan is very quiet, allowing the spotlight to be used even in noise-sensitive environments.

The beam angle is 15 degrees, but it can be widened to 40° or 60° by using magnetically attachable frost filters. Optional barn doors can also be screwed on, and these can likewise be combined with the frost filters.

Features:

- With a beam angle of 15°
- Variable color temperature 1800 K - 8000 K
- Very quiet working noise
- Good color rendering index (CRI)
- Control via stand-alone; IR remote control; DMX; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- 1 LED 200 W COB (chip-on-board) 5in1 RGBAL (homogenous color mix)
- Wash effect; strobe effect
- 9 integrated show programs
- Direct color selection for 28 preset colors
- Dimmer electronic

Logistic

EAN / GTIN: 4026397752991

Weight: 4,90 kg

Length: 0.45 m

Width: 0.31 m

Height: 0.28 m

- With double bracket
- Mains input and output for power linking up to 8 units
- For application areas such as: Stage; clubs/dancing school; wedding/gala/events; restaurants, bars and hotels; theater; rental; advertisement/Shop window
- Application possibility: Standing; suspended; on stand
- Can be operated in 3; 5; 7; 11 CH mode

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	135 W
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug
Cable construction:	3 x 1.0 mm² H05VV-F
Power output:	P-Con (grey), mounting version
Lamp type:	LED lamp
LED type:	1 x 200 W COB (chip-on-board) 5in1 RGBAL (homogenous color mix)
Flash rate:	0.5 - 23 Hz
DMX channels:	3; 5; 5; 7; 11
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	1 x cooling fan
Control:	Stand-alone; IR remote control; DMX; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W- DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	Light Captain
PWM frequency:	2900 Hz
DMX fail mode:	Blackout; hold; full on; static; auto
Beam angle:	15°
Beam angle (1/2 peak):	15°
Beam angle (1/10 peak):	34°
Color temperature:	1800K - 8000K adjustable
Color rendering index (CRI):	81 Ra
Lamp life:	50000 h
Housing color:	Black
Attachment system:	1x double bracket
Display type:	Monochrome LCD display
USB port:	Type A
Diameter mounting holes:	3 x Ø10mm
Material:	Aluminum casting
Dimensions:	Width: 25.95 cm Height: 37.65 cm
Weight:	4.10 kg
Noise classification:	Class 1 (very slight noise, suitable for noise- sensitive environments)

Battery:

1 x button cell 3.0 V CR2025 lithium manganese

Scope of delivery:

1 x spotlight
1 x power cord
1 x user manual
1 x remote control
1 x battery