

EUROLITE LED THA-40PC Theater Spot wh

Fanless PC spot (DMX), warm white 57 W LED, color rendering index (CRI) >90

Art. No.: 41602081

GTIN: 4026397578867



List price: 374.85 €

incl. 19% VAT.

Features:

- Very high color rendering index (CRI)
- Silent operation
- Flicker-free
- Control via RDM; stand-alone; DMX
- Dimmer electronic; dimmer curves with adjustable response; Dimmer speed (step response) adjustable
- Strobe effect
- 1 LED 57 W COB (chip-on-board) warm white (WW)
- The device is cooled by passive convection cooling
- With mounting bracket
- For application areas such as: Stage; decoration; wedding/gala/events; Trade fair and shop fitting; restaurants, bars and hotels; theater; video and photography; advertisement/Shop window
- Application possibility: Suspended; on stand
- Can be operated in 1; 2 CH mode
- With a beam angle of 11° - 48°

Logistic

EAN / GTIN: 4026397578867

Weight: 4,29 kg

Length: 0.34 m

Width: 0.27 m

Height: 0.22 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	40 W
Power connection:	Fixed power supply cord with safety plug
Lamp type:	LED lamp

LED type:	1 x 57 W COB (chip-on-board) warm white (WW)
DMX channels:	1; 2
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	RDM; stand-alone; DMX
Fixtures available for:	LED PC-Control 512; Light Captain; Light J; Colorchief
Projection:	Flicker-free
Beam angle:	11° - 48°
Beam angle (1/2 peak):	11 - 37°
Beam angle (1/10 peak):	17 - 48°
Color temperature:	3100K
Color rendering index (CRI):	91 Ra
Illuminance in Lux (lx):	Warm white (WW) 3m: 1656 lx, 6m: 424 lx
Housing color:	White
Attachment system:	Mounting bracket
Display type:	LCD display
Transport aid:	Rubber feet
Dimensions:	Length: 27.5 cm Width: 20.5 cm Depth: 25 cm
Weight:	3.84 kg
Noise classification:	Class 0 (no noise at all)

Scope of delivery:

1 x spotlight
1 x user manual
1 x barndoor