

EUROLITE LED THA-40PC DL Theater-Spot bk

Fanless PC spot (DMX), 57 W LED in neutral white, color rendering index (CRI) >90

Art. No.: 41602085

GTIN: 4026397613568



Features:

- Electronic dimmer (0-100%)
- Various dimmer curves with adjustable response
- Strobe effect
- Color temperature 4000 K
- With plano-convex lens
- Metal housing in black or white
- Rotatable barn doors and color filter frame included in the delivery
- 1 LED 57 W COB (chip-on-board) neutral white (NW)
- Can be operated in 1; 2 CH mode
- The device is cooled by passive convection cooling
- Control via RDM; DMX
- Flicker-free
- With a beam angle of 11° - 48°
- Very high color rendering index (CRI)
- With mounting bracket
- Rubber feet
- Silent operation

Logistic

EAN / GTIN: 4026397613568

Weight: 4,34 kg

Length: 0.34 m

Width: 0.21 m

Height: 0.27 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	40 W
Power connection:	Fixed power supply cord with safety plug

Lamp type:	LED lamp
LED type:	1 x 57 W COB (chip-on-board) neutral white (NW)
DMX channels:	1; 2
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	RDM; DMX
Fixtures available for:	LED PC-Control 512; Light Captain; Light J
Projection:	Flicker-free
Beam angle:	11° - 48°
Beam angle (1/2 peak):	11 - 37°
Beam angle (1/10 peak):	17 - 48°
Color temperature:	4000K
Color rendering index (CRI):	90 Ra
Illuminance in Lux (lx):	3m: 1863 lx, 6m: 481 lx
Housing color:	Black
Attachment system:	Mounting bracket
Transport aid:	Rubber feet
Dimensions:	Length: 27.5 cm Width: 20.5 cm Depth: 25 cm
Weight:	3.92 kg
Noise classification:	Class 0 (no noise at all)

Scope of delivery:

1 x barndoor