

EUROLITE LED THA-60PC Theater Spot

Spot with 60 W COB LED (RGBW) and plano-convex lens, extremely quiet, DMX

Art. No.: 41602110

GTIN: 4026397566604



Features:

- With plano-convex lens
- Compact design
- 1 LED 60 W COB (chip-on-board) 4in1 RGBW (homogenous color mix)
- Dimmer electronic; color change adjustable; color fade adjustable; dimmer curves with adjustable response; Dimmer speed (step response) adjustable
- Strobe effect
- Can be operated in 5; 6; 7 CH mode
- The device is cooled by temperature-controlled fan
- Control via stand-alone; DMX
- Flicker-free
- With a beam angle of 7° - 48°
- With mounting bracket
- LCD display
- For application areas such as: Stage; clubs/dancing school; wedding/gala/events; restaurants, bars and hotels; theater; advertisement/Shop window
- Very quiet working noise
- Application possibility: Suspended; on stand

Logistic

EAN / GTIN: 4026397566604

Weight: 4,19 kg

Length: 0.36 m

Width: 0.21 m

Height: 0.27 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	60 W
Power connection:	Fixed power supply cord with safety plug

Lamp type:	LED lamp
LED type:	1 x 60 W COB (chip-on-board) 4in1 RGBW (homogenous color mix)
DMX channels:	5; 6; 7
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	Stand-alone; DMX
Fixtures available for:	Light´ J; LED PC-Control 512; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; Colorchief
Projection:	Flicker-free
Beam angle:	7° - 48°
Beam angle (1/2 peak):	7 - 39°
Beam angle (1/10 peak):	14 - 48°
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	LCD display
Dimensions:	Length: 33.4 cm Width: 19.6 cm Depth: 17.3 cm
Weight:	3.74 kg
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments)

Scope of delivery:

1 x spotlight
 1 x barndoor
 1 x user manual
 1 x filter frame