

EUROLITE LED THA-100F MK3 Theater Spot

Fresnel spotlight (fresnel lens), warm white 100 W LED, CRI >90, quiet, DMX

Art. No.: 41602127

GTIN: 4026397690453



List price: 653.31 €

incl. 19% VAT.

Features:

- Very high color rendering index (CRI)
- Very quiet working noise
- With a beam angle of 8° - 55°
- Flicker-free
- Control via stand-alone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- 1 LED 100 W COB (chip-on-board) warm white (WW)
- Dimmer electronic; dimmer curves with adjustable response; pulse-width modulation variable; Dimmer speed (step response) adjustable
- Strobe effect
- With mounting bracket
- Mains input and output for power linking up to 8 units
- For application areas such as: Stage; wedding/gala/events; Trade fair and shop fitting; theater; rental; video and photography
- Application possibility: Suspended; on stand
- Can be operated in 1; 3 CH mode

Logistic

EAN / GTIN: 4026397690453

Weight: 9,30 kg

Length: 0.49 m

Width: 0.40 m

Height: 0.38 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 95 W

Protection class: Protection class I

Power connection:	Mains input via P-Con (blue), mounting version included
Power output:	P-Con (grey), mounting version
Fuse:	5 x 20 mm, T 2 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 100 W COB (chip-on-board) warm white (WW)
Flash rate:	20 Hz
DMX channels:	1; 3
DMX input:	3-pin XLR (M) mounting version 5-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version 5-pin XLR (F) mounting version
Cooling:	Low-noise cooling fan
Control:	Stand-alone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	Light Captain
Projection:	Flicker-free
Beam angle:	8° - 55°
Beam angle (1/2 peak):	8 - 40°
Beam angle (1/10 peak):	16 - 55°
Color temperature:	3000K
Color rendering index (CRI):	96 Ra
Luminous flux:	5384 lm
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	LCD display
Transport aid:	Rubber feet
Material:	Aluminum casting; metal
Dimensions:	Length: 35.0 cm Width: 31.5 cm Height: 39.5 cm
Weight:	7.15 kg
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments)
Energy efficiency class (A - G):	G
EPREL-Nr:	1243837
Cable construction:	3 x 1.5 mm² H05VV-F
Cable length:	Approx. 1.8 m
Diameter mounting holes:	5 x Ø13mm
Material:	Aluminum casting, 6 mm
Material:	Aluminum, 1 mm
Ring diameter:	Outside: 172 mm Inside: 150 mm
Dimensions:	Width: 42.2 cm Height: 42.5 cm

Material:	Aluminum, 1 mm
Dimensions:	Width: 18.5 cm
	Height: 18.5 cm
	Diameter: Ø 15.2 cm

Scope of delivery:

- 1 x spotlight
- 1 x power cord
- 1 x barndoor
- 1 x filter frame
- 1 x user manual