

EUROLITE LED THA-150F Theater Spot

Fresnel spotlight, dim to warm, 170 W warm white/amber LED, CRI >90, quiet, DMX

Art. No.: 41602133

GTIN: 4026397654998



List price: 903.21 €

incl. 19% VAT.

Features:

- New LED technology that simulates the color temperature curve of a halogen lamp when dimming
- Very high color rendering index (CRI)
- Zoom motor driven
- With a beam angle of 8° - 55°
- Exact 16 bit resolution at Dimmer
- Flicker-free
- Control via RDM; DMX
- 1 LED 170 W COB (chip-on-board) Dim to warm (homogenous color mix)
- Color blend stepless; Dimmer electronic; Dimmer speed (step response) adjustable; dimmer curves adjustable
- Strobe effect
- Rugged metal housing
- With mounting bracket
- Mains input and output for power linking up to 8 units
- For application areas such as: Stage; wedding/gala/events; Trade fair and shop fitting; theater; rental; video and photography
- Application possibility: Suspended; on stand
- Can be operated in 2; 6; 7 CH mode

Logistic

EAN / GTIN: 4026397654998

Weight: 11,90 kg

Length: 0.61 m

Width: 0.37 m

Height: 0.44 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 150 W

Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug included
Power output:	P-Con (grey), mounting version
Lamp type:	LED lamp
LED type:	1 x 170 W COB (chip-on-board) Dim to warm (homogenous color mix)
Flash rate:	1.6 - 12 Hz
Equipment:	Zoom motor driven
DMX channels:	2; 6; 7
DMX input:	1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	RDM; DMX
Fixtures available for:	Light J; Light Captain
Projection:	Flicker-free
PWM frequency:	3600 Hz
Beam angle:	8° - 55°
Beam angle (1/2 peak):	8 - 39°
Beam angle (1/10 peak):	12 - 55°
Color rendering index (CRI):	96 Ra
Luminous flux:	5093 lm
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	LCD display
Transport aid:	Rubber feet
Material:	Aluminum casting; metal
Slot for spot length:	20 cm x 20 cm
Dimensions:	Length: 45.7 cm Width: 33.6 cm Height: 39.8 cm
Weight:	9.40 kg
Noise classification:	Class 2 (slight noise)
Energy efficiency class (A - G):	G
EPREL-Nr:	1243870
Diameter mounting holes:	5 x Ø10mm
Material:	Aluminum casting, 6.5 mm
Cable construction:	3 x 1.5 mm² H05VV-F
Cable length:	Approx. 1.3 m
Material:	Aluminum, 1.5 mm; metal, 1 mm
Ring diameter:	Outside: 198 mm Inside: 220 mm
Dimensions:	Width: 50.5 cm Depth: 4.2 cm

	Height: 50.5 cm
Material:	Aluminum, 1 mm
Dimensions:	Width: 22.5 cm
	Height: 22.5 cm
	Diameter: Ø 18 cm

Scope of delivery:

- 1 x spotlight
- 1 x power cord
- 1 x barndoor
- 1 x filter frame
- 1 x user manual