

EUROLITE LED THA-250F 2700K-6500K Theater Spot

Fresnel spotlight, 250 W LED, variable color temperature, CRI >90, zoom

Art. No.: 41602135

GTIN: 4026397610833



Features:

- 1 LED 250 W COB (chip-on-board) 2in1 CW/WW (homogenous color mix)
- Zoom motor driven; focus manual
- Dimmer electronic
- Strobe effect
- Can be operated in 4; 5 CH mode
- The device is cooled by temperature-controlled fan
- Control via DMX
- Flicker-free
- With a beam angle of 6° - 46°
- Variable color temperature 2700 K - 6500 K
- Very high color rendering index (CRI)
- With mounting bracket
- LCD display
- Mains input and output for power linking up to 8 units

Logistic

EAN / GTIN: 4026397610833

Weight: 11,50 kg

Length: 0.52 m

Width: 0.33 m

Height: 0.32 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	200 W
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x P-Con (grey), mounting version
Lamp type:	LED lamp

LED type:	1 x 250 W COB (chip-on-board) 2in1 CW/WW (homogenous color mix)
Equipment:	Zoom motor driven; focus manual
DMX channels:	4; 5
DMX input:	1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	DMX
Fixtures available for:	LED PC-Control 512; Light´J; Light Captain
Projection:	Flicker-free
Beam angle:	6° - 46°
Beam angle (1/2 peak):	6 - 25°
Beam angle (1/10 peak):	20 - 46°
Color temperature:	2700K - 6500K adjustable
Color rendering index (CRI):	96 Ra
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	LCD display
Dimensions:	Length: 43.5 cm Width: 27.5 cm Height: 38.5 cm
Weight:	10.45 kg
Noise classification:	Class 2 (slight noise)

Scope of delivery:

1 x spotlight
 1 x user manual
 1 x power cord
 1 x barndoor
 1 x XLR cable
 1 x plug (male)