

EUROLITE SUNSET IP BAR 12 Blinder dim2warm

Weather-proof (IP65) bar with twelve 30W LED units and excellent tungsten simulation

Art. No.: 41604100

GTIN: 4026397755527



List price: 712.81 €

incl. 19% VAT.

Description:

This weatherproof bar fixture is equipped with LEDs that mimic the behavior of traditional incandescent lamps. When dimmed, the color temperature changes; as brightness decreases, the warm white light becomes progressively warmer, taking on a golden tone.

The Sunset IP Bar 12 simulates this effect very convincingly. When dimmed down to zero, the light fades out smoothly into a golden color. Even at low brightness levels, it maintains the characteristic warm tone of a halogen lamp.

The twelve LEDs, each with 30 W, can be controlled individually, allowing for both powerful blinder effects and dynamic chase effects.

Logistic

EAN / GTIN: 4026397755527

Weight: 9,25 kg

Length: 1.09 m

Width: 0.23 m

Height: 0.23 m

Features:

- Suitable for outdoor use IP65
- Blinder effect
- Very quiet working noise
- Flicker-free
- Control via stand-alone; DMX; RDM; master/slave function
- 5 integrated show programs
- Dimmer electronic; dimmer curves adjustable; Dimmer speed (step response) adjustable; pulse-width modulation adjustable; Dim to warm
- 36 LEDs 10 W warm white (WW)
12 segments controlled separately
- 48 LEDs 0.6 W red (R)
12 segments controlled separately
- 48 LEDs 1 W amber (A)
12 segments controlled separately
- With mounting bracket; with omega bracket
- The device is cooled by passive convection cooling

- Mains input and output for power linking up to 8 units
- Built with SEETRONIC connector
- With pressure compensation membrane
- For application areas such as: Stage; clubs/dancing school; wedding/gala/events; restaurants, bars and hotels; theater
- Application possibility: Standing; suspended
- Can be operated in 1; 4; 6; 12; 16; 21; 24; 34 CH mode

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	230 W
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug
Cable construction:	3 x 2.5 mm ² H07RN-F
Power output:	IP T-Con (F) mounting version
Lamp type:	LED lamp
LED type:	36 x 10 W warm white (WW) 48 x 0.6 W red (R) 48 x 1 W amber (A)
Flash rate:	1 - 33 Hz
DMX channels:	1; 4; 6; 12; 16; 21; 24; 34
DMX input:	3-pin XLR (M) mounting version IP 5-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP 5-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; RDM; master/slave function
Fixtures available for:	Light Captain; GDTF (GrandMA3)
Projection:	Flicker-free
DMX features:	RDM For bidirectional communication over the DMX line
DMX fail mode:	Hold; blackout
Housing color:	Black
Attachment system:	2x mounting bracket 2x omega bracket
Display type:	Multicolor LCD display
Diameter mounting holes:	2 x Ø12mm
Use of brands:	Built with SEETRONIC connector
Material:	Aluminum casting
Dimensions:	Length: 100.5 cm Width: 14.0 cm Height: 18.0 cm
Weight:	8.00 kg
Noise classification:	Class 1 (very slight noise, suitable for noise- sensitive environments)

Scope of delivery:

1 x spotlight
1 x user manual
1 x power cord
2 x omega bracket