

EUROLITE IP Audience Blinder 2x100W LED COB RGB+WW

Weather-proof audience blinder with 2x 100 W COB LED in RGB+warm white

Art. No.: 41604160

GTIN: 4026397718386



Features:

- 2 LEDs 100 W COB (chip-on-board) 4in1 RGB/WW
 LEDs controlled separately
- Color blend stepless; Dimmer electronic
- Strobe effect
- 3 integrated show programs
- Can be operated in 4; 6; 8; 12 CH mode
- The device is cooled by temperature-controlled fan
- Control via stand-alone; master/slave function; DMX
- Flicker-free
- With a beam angle of 28°
- With mounting bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- Suitable for outdoor use IP65
- With pressure compensation membrane
- For application areas such as: Stage; clubs/dancing school; wedding/gala/events; restaurants, bars and hotels; rental
- Application possibility: Suspended; on stand

Logistic

EAN / GTIN: 4026397718386

Weight: 8,60 kg

Length: 0.48 m

Width: 0.30 m

Height: 0.30 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 180 W

IP classification: IP65

Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IP T-Con (F) mounting version
Lamp type:	LED lamp
LED type:	2 x 100 W COB (chip-on-board) 4in1 RGB/WW
Flash rate:	1 - 25 Hz
DMX channels:	4; 6; 8; 12
DMX input:	3-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP
Cooling:	Temperature-controlled fan
Control:	Stand-alone; master/slave function; DMX
Fixtures available for:	Light Captain; Light J; Colorchief
Projection:	Flicker-free
Beam angle:	28°
Beam angle (1/2 peak):	28°
Beam angle (1/10 peak):	75°
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Width: 40.3 cm Depth: 19.5 cm Height: 29.8 cm
Weight:	7.85 kg
Noise classification:	Class 2 (slight noise)

Scope of delivery:

1 x spotlight
 1 x user manual
 1 x power cord
 1 x XLR cable