

## EUROLITE IP Audience Blinder 2x100W LED COB WW

Weather-proof audience blinder with 2x 100 W COB LED in warm white

Art. No.: 41604170

GTIN: 4026397720303



**List price: 593.81 €**

incl. 19% VAT.

### Features:

- 2 LEDs COB (chip-on-board) warm white (WW)<BR> LEDs controlled separately
- Dimmer electronic
- Strobe effect
- 3 integrated show programs
- Can be operated in 2; 6 CH mode
- The device is cooled by low-noise cooling fan
- Control via stand-alone; master/slave function; DMX
- Flicker-free
- With a beam angle of 28°
- Good color rendering index (CRI)
- With mounting bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- Suitable for outdoor use IP65
- With pressure compensation membrane
- For application areas such as: Stage; theater; rental
- Application possibility: Suspended; on stand

### Logistic

EAN / GTIN: 4026397720303

Weight: 8,55 kg

Length: 0.47 m

Width: 0.30 m

Height: 0.30 m

### Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 170 W

IP classification: IP65

|                              |                                                                                             |
|------------------------------|---------------------------------------------------------------------------------------------|
| Protection class:            | Protection class I                                                                          |
| Power connection:            | Mains input via IP T-Con (M) mounting version power supply cord with safety plug (provided) |
| Power output:                | IP T-Con (F) mounting version                                                               |
| Lamp type:                   | LED lamp                                                                                    |
| LED type:                    | 2 x COB (chip-on-board) warm white (WW)                                                     |
| Flash rate:                  | 1 - 25 Hz                                                                                   |
| DMX channels:                | 2; 6                                                                                        |
| DMX input:                   | 3-pin XLR (M) mounting version IP                                                           |
| DMX output:                  | 3-pin XLR (F) mounting version IP                                                           |
| Cooling:                     | Low-noise cooling fan                                                                       |
| Control:                     | Stand-alone; master/slave function; DMX                                                     |
| Fixtures available for:      | Light Captain                                                                               |
| Projection:                  | Flicker-free                                                                                |
| Beam angle:                  | 28°                                                                                         |
| Beam angle (1/2 peak):       | 28°                                                                                         |
| Beam angle (1/10 peak):      | 75°                                                                                         |
| Color temperature:           | 3100K                                                                                       |
| Color rendering index (CRI): | 89 Ra                                                                                       |
| Housing color:               | Black                                                                                       |
| Attachment system:           | Mounting bracket                                                                            |
| Display type:                | 4 digit 7-segment LED display                                                               |
| Dimensions:                  | Width: 40.3 cm<br>Depth: 19.5 cm<br>Height: 29.8 cm                                         |
| Weight:                      | 7.80 kg                                                                                     |
| Noise classification:        | Class 2 (slight noise)                                                                      |

## Scope of delivery:

1 x spotlight  
 1 x user manual  
 1 x power cord  
 1 x XLR cable