

EUROLITE IP Audience Blinder 2x100W LED COB WW

Weather-proof audience blinder with 2x 100 W COB LED in warm white

Art. No.: 41604170

GTIN: 4026397720303



Features:

- 2 LEDs COB (chip-on-board) warm white (WW)
 LEDs controlled separately
- Dimmer electronic
- Strobe effect
- 3 integrated show programs
- Can be operated in 2; 6 CH mode
- The device is cooled by low-noise cooling fan
- Control via stand-alone; master/slave function; DMX
- Flicker-free
- With a beam angle of 28°
- Good color rendering index (CRI)
- With mounting bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- Suitable for outdoor use IP65
- With pressure compensation membrane
- For application areas such as: Stage; theater; rental
- Application possibility: Suspended; on stand

Logistic

EAN / GTIN: 4026397720303

Weight: 8,55 kg

Length: 0.47 m

Width: 0.30 m

Height: 0.30 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
---------------	------------------------

Power consumption:	170 W
--------------------	-------

IP classification:	IP65
--------------------	------

Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug (provided)
Power output:	IP T-Con (F) mounting version
Lamp type:	LED lamp
LED type:	2 x COB (chip-on-board) warm white (WW)
Flash rate:	1 - 25 Hz
DMX channels:	2; 6
DMX input:	3-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP
Cooling:	Low-noise cooling fan
Control:	Stand-alone; master/slave function; DMX
Fixtures available for:	Light Captain
Projection:	Flicker-free
Beam angle:	28°
Beam angle (1/2 peak):	28°
Beam angle (1/10 peak):	75°
Color temperature:	3100K
Color rendering index (CRI):	89 Ra
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Width: 40.3 cm Depth: 19.5 cm Height: 29.8 cm
Weight:	7.80 kg
Noise classification:	Class 2 (slight noise)

Scope of delivery:

1 x spotlight
 1 x user manual
 1 x power cord
 1 x XLR cable