

EUROLITE Audience Blinder 2x100W LED COB CW/WW

Audience blinder, wide beam, warm/cold white

Art. No.: 41606122

GTIN: 4026397622096



Features:

- Variable color temperature 3200 K - 6400 K
- Flicker-free
- Control via DMX; sound to light via microphone; master/slave function; stand-alone
- Strobe effect
- 2 LEDs 100 W COB (chip-on-board) 2in1 CW/WW (homogenous color mix)
- With mounting bracket
- Energy-saving, durable and environmentally friendly
- Mains input and output for power linking up to 8 units
- For application areas such as: Stage; theater; rental
- Application possibility: Suspended; on stand
- Can be operated in 4; 8 CH mode

Logistic

EAN / GTIN: 4026397622096

Weight: 4,05 kg

Length: 0.45 m

Width: 0.22 m

Height: 0.29 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	200 W
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug included
Power output:	P-Con (grey), mounting version
Lamp type:	LED lamp

LED type:	2 x 100 W COB (chip-on-board) 2in1 CW/WW (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	4; 8
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	3 x cooling fan
Control:	DMX; sound to light via microphone; master/slave function; stand-alone
Fixtures available for:	Light´J; Light Captain; Colorchief
Projection:	Flicker-free
Beam angle (1/2 peak):	30°
Beam angle (1/10 peak):	80°
Color temperature:	3200K - 6400K adjustable
Luminous flux:	8500 lm
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Width: 37 cm Depth: 15 cm Height: 24 cm
Weight:	3.74 kg
Noise classification:	Class 2 (slight noise)
Energy efficiency class (A - G):	G
Cable construction:	3 x 1.5 mm² H05VV-F
Diameter mounting holes:	3 x Ø10mm
Material:	Metal, 2 mm

Scope of delivery:

1 x spotlight
1 x power cord
1 x user manual