EUROLITE Audience Blinder 4x50W LED COB 3200K

PRO audience blinder with 4 x 50 W COB LED

Art. No.: 41606125

GTIN: 4026397467062











Features:

- 3200 K color temperature
- 1, 2, 4, 6 or 7 DMX channels selectable for various applications
- Each LED can be controlled individually
- Functions: built-in programs and strobe effect with variable speed, dimmer, Master/Slave
- Different dimmer curves and dimmer speed adjustable
- DMX-controlled operation or stand-alone operation with Master/Slave function
- For use on stages, catwalks, crossbeam systems, or decoration
- Swivelable lamp rows
- Rugged housing and an appealing design
- Comfortable addressing and setting via control panel with LC display and four operating buttons
- Locking possibility at the mounting bracket
- Power connection via Neutrik PowerCon jack and included power cable
- Feed-through output allows to power another device
- After every 8 devices the fixtures must have a renewed connection with the power mains
- DMX control via every standard DMX controller
- Can be operated in 2; 1 CH mode

Logistic

EAN / GTIN: 4026397467062
Weight: 11,00 kg
Length: 0.53 m
Width: 0.51 m
Heigth: 0.26 m

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	250 W
Flash rate:	1 - 20 Hz
DMX channels:	2; 1

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Fixtures available for:	Light´J; Light Captain
Beam angle (1/2 peak):	60°
Color temperature:	3200K
Dimensions:	Width: 40 cm Depth: 49.5 cm Height: 17.5 cm
Weight:	9.10 kg
DMX channels:	1/2/4/6/7
DMX connection:	5-pin and 3-pin XLR
Flash-rate:	20 Hz
LED number:	4
LED type:	Array 50 W, white
Color temperature:	3200 K
Beam angle:	60°
Dimensions (L x W x H):	175 x 400 x 415 mm

Scope of delivery:

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.