

EUROLITE Audience Blinder 4x100W LED COB CW/WW

Audience blinder, wide beam 4 x 100 W COB LED (warm/cold white)

Art. No.: 41606147

GTIN: 4026397622058



List price: 653.31 €

incl. 19% VAT.

Features:

- Swivel lamp rows
- Variable color temperature 3200 K - 6400 K
- With a beam angle of 45°
- Flicker-free
- Control via stand-alone; DMX; master/slave function
- 4 LEDs 100 W COB (chip-on-board) 2in1 CW/WW (homogenous color mix)
- Strobe effect
- 4 integrated show programs
- Energy-saving, durable and environmentally friendly
- With mounting bracket
- Mains input and output for power linking up to 8 units
- For application areas such as: Stage; theater; rental
- Application possibility: Suspended; on stand
- Can be operated in 2; 8; 12 CH mode

Logistic

EAN / GTIN: 4026397622058

Weight: 7,60 kg

Length: 0.58 m

Width: 0.46 m

Height: 0.18 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	350 W
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x P-Con (grey), mounting version

Fuse:	T 10 A fuse fix on board
Lamp type:	LED lamp
LED type:	4 x 100 W COB (chip-on-board) 2in1 CW/WW (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	2; 8; 12
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	6 x cooling fan
Control:	Stand-alone; DMX; master/slave function
Fixtures available for:	Light J; Light Captain
Projection:	Flicker-free
Beam angle:	45°
Beam angle (1/2 peak):	45°
Color temperature:	3200K - 6400K adjustable
Luminous flux:	16600 lm
Housing color:	Black matte
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Material:	Metal, 1 mm
Dimensions:	Width: 42 cm Depth: 49.5 cm Height: 12.5 cm
Weight:	7.00 kg
Noise classification:	Class 2 (slight noise)
Energy efficiency class (A - G):	G
Diameter mounting holes:	3 x Ø13mm
Material:	Metal, 2 mm

Scope of delivery:

1 x device
1 x power cord
1 x user manual