

EUROLITE AKKU Multiflood IP 8x10W RGBW Wash CRMX

Art. No.: 41606258

Silent battery-powered IP65 floodlight with RGBW LEDs, CRMX, diffuser cover, barn doors, IR remote control

GTIN: 4026397727562



List price: 831.81 €

incl. 19% VAT.

Features:

- Integrated wireless receiver for CRMX operation
- Additional frost filter provides a wide, soft and homogeneous light
- 4 barn doors to avoid blinding the audience and for protection during transport
- Cordless, flexible and versatile
- Battery operation up to 9h depending on program used
- 8 LEDs 10 W SMD 5050 4in1 RGBW (homogenous color mix)
- Emergency lighting function in case of power failure; color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) with adjustable response; white balance
- Strobe effect
- 36 integrated show programs
- Direct color selection for 15 preset colors
- Can be operated in 3; 4; 6; 8; 11 CH mode
- The device is cooled by passive convection cooling
- Control via DMX; W-DMX by wireless solution; CRMX by LumenRadio; master/slave function; RDM; stand-alone; IR remote control
- Flicker-free
- With a beam angle of 10°
- With mounting bracket; with omega bracket
- OLED display
- Display of the remaining battery life for the current setting
- Charge status indicator
- Mains input and output for power linking up to 8 units
- Suitable for outdoor use IP65
- With pressure compensation membrane
- With a KENSINGTON LOCK theft protection

Logistic

EAN / GTIN: 4026397727562

Weight: 8,75 kg

Length: 0.37 m

Width: 0.27 m

Height: 0.30 m

- For application areas such as: Stage; architecture; wedding/gala/events; Trade fair and shop fitting; theater; rental
- Silent operation
- Application possibility: Suspended; on stand; standing
- 3 buttons on the remote control for saving your own settings

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug Battery/battery pack
Power output:	IP T-Con (F) mounting version
Battery pack type:	1 x lithium ion 18.5 V, 15600 mAh, 288.6 Wh
Battery pack:	Battery operation up to 9h depending on program used Recharging time 4.5h
Lamp type:	LED lamp
LED type:	8 x 10 W SMD 5050 4in1 RGBW (homogenous color mix)
Flash rate:	1 - 23 Hz
DMX channels:	3; 4; 6; 8; 11
DMX input:	3-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	DMX; W-DMX by wireless solution; CRMX by LumenRadio; master/slave function; RDM; stand-alone; IR remote control
Fixtures available for:	Light Captain; LED PC-Control 512; Light´J; Colorchief
Projection:	Flicker-free
Carrier frequency:	2.4 GHz
Beam angle:	10°
Beam angle (1/2 peak):	10° Frost filter 25°
Beam angle (1/10 peak):	25° Frost filter 55°
Housing color:	Black
Attachment system:	Mounting bracket Omega bracket
Display type:	OLED display
Display reading:	Battery runtime calculation , charge status indicator
Theft protection:	KENSINGTON LOCK
Dimensions:	Length: 31.9 cm Width: 14 cm Height: 24.8 cm
Weight:	7.85 kg

Noise classification:	Class 0 (no noise at all)
Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in

Scope of delivery:

- 1 x device
- 1 x user manual
- 1 x power cord
- 1 x remote control
- 1 x battery
- 1 x frost filter
- 1 x omega bracket
- 1 x barndoor
- 1 x declaration of conformity