

## EUROLITE LED Pixel Matrix Bar 10 RGB/WW

Matrix bar with RGB/WW LEDs, pixel control & macros for sequences

Art. No.: 41606360

GTIN: 4026397742527



### Features:

- Create sensational light effect surfaces by connecting several devices
- 10 LEDs 12 W SMD 5050 4in1 RGB/WW (homogenous color mix)<BR> LEDs controlled separately
- Dimmer electronic; color change; color fade; color animations with two adjustable colors
- Strobe effect; Blinder effect; matrix effect
- 9 integrated show programs
- Can be operated in 4; 10; 15; 40; 42 CH mode
- The device is cooled by passive convection cooling
- Control via RDM; Art-Net; stand-alone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); master/slave function; sound to light
- Flicker-free
- With a beam angle of 45°
- With bracket for floor use
- Multicolor LCD display
- Mains input and output for power linking up to 8 units
- For application areas such as: Stage; clubs/dancing school; wedding/gala/events; mobile djs / entertainer; restaurants, bars and hotels; rental
- Very quiet working noise
- Application possibility: Standing; suspended; on stand

### Logistic

EAN / GTIN: 4026397742527

Weight: 6,85 kg

Length: 0.97 m

Width: 0.19 m

Heigh: 0.18 m

### Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

|                          |                                                                                                                                                                                                   |
|--------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power consumption:       | 60 W                                                                                                                                                                                              |
| Protection class:        | Protection class I                                                                                                                                                                                |
| Power connection:        | Mains input via P-Con (blue), mounting version<br>power supply cord with safety plug                                                                                                              |
| Power output:            | P-Con (grey), mounting version                                                                                                                                                                    |
| Fuse:                    | 5 x 20 mm, T 2 A fuse replaceable                                                                                                                                                                 |
| Lamp type:               | LED lamp                                                                                                                                                                                          |
| LED type:                | 10 x 12 W SMD 5050 4in1 RGB/WW<br>(homogenous color mix)                                                                                                                                          |
| DMX channels:            | 4; 10; 15; 40; 42                                                                                                                                                                                 |
| DMX input:               | 3-pin XLR (M) mounting version                                                                                                                                                                    |
| DMX output:              | 3-pin XLR (F) mounting version                                                                                                                                                                    |
| Network connection:      | Protocol: Art-Net 3 via 2x RJ-45 E-Con (F)<br>mounting version                                                                                                                                    |
| Cooling:                 | Passive convection cooling                                                                                                                                                                        |
| Control:                 | RDM; Art-Net; stand-alone; DMX; QuickDMX via<br>USB (optional); W-DMX by wireless solution via<br>USB (optional); CRMX by LumenRadio via USB<br>(optional); master/slave function; sound to light |
| Fixtures available for:  | Light Captain                                                                                                                                                                                     |
| Projection:              | Flicker-free                                                                                                                                                                                      |
| PWM frequency:           | 2900 Hz                                                                                                                                                                                           |
| DMX fail mode:           | Blackout; hold                                                                                                                                                                                    |
| Beam angle:              | 45°                                                                                                                                                                                               |
| Beam angle (1/2 peak):   | 45°                                                                                                                                                                                               |
| Beam angle (1/10 peak):  | 82°                                                                                                                                                                                               |
| Housing color:           | Black                                                                                                                                                                                             |
| Attachment system:       | Bracket for floor use                                                                                                                                                                             |
| Display type:            | Multicolor LCD display                                                                                                                                                                            |
| USB port:                | Type A                                                                                                                                                                                            |
| Diameter mounting holes: | 3 x Ø10mm                                                                                                                                                                                         |
| Material:                | Metal                                                                                                                                                                                             |
| Dimensions:              | Length: 90 cm<br>Depth: 13.5 cm<br>Height: 14.9 cm                                                                                                                                                |
| Weight:                  | 6.00 kg                                                                                                                                                                                           |
| Noise classification:    | Class 1 (very slight noise, suitable for noise-<br>sensitive environments)                                                                                                                        |

## Scope of delivery:

1 x bar  
1 x power cord  
1 x user manual