

## EUROLITE LED IP Atmo Bar 10

Weather-proof blinder bar with pixel control and colored atmospheric light in the reflector

Art. No.: 41606410

GTIN: 4026397719611



**List price: 891.31 €**

incl. 19% VAT.

### Features:

- 10 LEDs 24 W COB (chip-on-board) CW/WW (homogenous color mix)<BR> LEDs controlled separately
- 200 LEDs 0.2 W SMD 3528 3in1 RGB (homogenous color mix)<BR>10 segments controlled separately
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; dimmer curves with adjustable response; white balance adjustable
- Strobe effect
- 10 integrated show programs
- Can be operated in 10; 14; 20; 50; 59 CH mode
- The device is cooled by low-noise cooling fan
- Control via stand-alone; master/slave function; DMX; Art-Net; RDM
- Flicker-free
- With a beam angle of 28°
- Variable color temperature 1800 K - 6000 K
- With mounting bracket; with omega bracket
- OLED display
- Mains input and output for power linking up to 4 units
- Suitable for outdoor use IP65
- With pressure compensation membrane
- For application areas such as: Stage; clubs/dancing school; wedding/gala/events; rental
- Very quiet working noise
- Application possibility: Suspended

### Logistic

EAN / GTIN: 4026397719611

Weight: 11,85 kg

Length: 1.10 m

Width: 0.28 m

Height: 0.25 m

**Technical specifications:**

|                         |                                                                                                                              |
|-------------------------|------------------------------------------------------------------------------------------------------------------------------|
| Power supply:           | 100-240 V AC, 50/60 Hz                                                                                                       |
| Power consumption:      | 315 W                                                                                                                        |
| IP classification:      | IP65                                                                                                                         |
| Protection class:       | Protection class I                                                                                                           |
| Power connection:       | Mains input via IP T-Con (M) mounting version<br>power supply cord with safety plug (provided)                               |
| Power output:           | IP T-Con (F) mounting version                                                                                                |
| Lamp type:              | LED lamp                                                                                                                     |
| LED type:               | 10 x 24 W COB (chip-on-board) CW/WW<br>(homogenous color mix)<br><br>200 x 0.2 W SMD 3528 3in1 RGB (homogenous<br>color mix) |
| DMX channels:           | 10; 14; 20; 50; 59                                                                                                           |
| DMX input:              | 3-pin XLR (M) mounting version IP                                                                                            |
| DMX output:             | 3-pin XLR (F) mounting version IP                                                                                            |
| Cooling:                | Low-noise cooling fan                                                                                                        |
| Control:                | Stand-alone; master/slave function; DMX; Art-<br>Net; RDM                                                                    |
| Fixtures available for: | Light Captain; LED PC-Control 512                                                                                            |
| Projection:             | Flicker-free                                                                                                                 |
| Beam angle:             | 28°                                                                                                                          |
| Beam angle (1/2 peak):  | 28°                                                                                                                          |
| Beam angle (1/10 peak): | 63                                                                                                                           |
| Color temperature:      | 1800K - 6000K adjustable                                                                                                     |
| Housing color:          | Black                                                                                                                        |
| Attachment system:      | Mounting bracket<br>2x omega bracket                                                                                         |
| Display type:           | OLED display                                                                                                                 |
| Connections:            | 2 x RJ-45 E-Con (F) mounting version                                                                                         |
| Dimensions:             | Length: 101.0 cm<br>Depth: 12.5 cm<br>Height: 24 cm                                                                          |
| Weight:                 | 10.50 kg                                                                                                                     |
| Noise classification:   | Class 1 (very slight noise, suitable for noise-<br>sensitive environments)                                                   |

**Scope of delivery:**

- 1 x bar
- 1 x user manual
- 1 x power cord
- 2 x omega bracket
- 1 x XLR cable