

## EUROLITE LED PMC-8x30W COB RGB MFL

COB Performance Cluster with 25° beam angle

Art. No.: 41606450

GTIN: 4026397507805



**The article is no longer in our assortment.**

### Features:

- Operable in stand-alone mode via control panel with LCD screen or in DMX mode
- Equipped with 8 x 30 W COB LEDs in the colors red, green and blue
- Each LED can be controlled individually
- Functions: Static colors, RGB color mixture, automatic color change, internal programs, dimmer and strobe settings via DMX, Master/Slave
- Dimmer speed (step response) controllable
- Adjustable white balance
- Comfortable addressing and setting via control panel with LC display and four operating buttons
- Ideal as floor spot via base for standing installation
- Locking possibility at the mounting bracket
- With barn doors
- Neutrik powerCON terminals for power linking up to 8 units
- 8 LEDs 30 W COB (chip-on-board) 3in1 RGB (homogenous color mix)
- Strobe effect
- Can be operated in 3; 4; 5; 6; 12; 24; 28; 33 CH mode
- Control via DMX; sound to light via microphone; RDM
- With a beam angle of 25°

### Logistic

EAN / GTIN: 4026397507805

Weight: 7,60 kg

Length: 0.41 m

Width: 0.24 m

Height: 0.29 m

### Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 220.00 W

|                         |                                                                                                                                 |
|-------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| Power connection:       | Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided)                                 |
| Power output:           | 1 x PowerCON (grey), mounting version                                                                                           |
| Lamp type:              | LED lamp                                                                                                                        |
| LED type:               | 8 x 30 W COB (chip-on-board) 3in1 RGB (homogenous color mix)                                                                    |
| Flash rate:             | 0 - 18 Hz                                                                                                                       |
| DMX channels:           | 3; 4; 5; 6; 12; 24; 28; 33                                                                                                      |
| DMX input:              | 1 x 3-pin XLR (M) mounting version<br>1 x 5-pin XLR (M) mounting version                                                        |
| DMX output:             | 1 x 3-pin XLR (F) mounting version<br>1 x 5-pin XLR (F) mounting version                                                        |
| Control:                | DMX; sound to light via microphone; RDM                                                                                         |
| Fixtures available for: | Light J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain |
| Beam angle:             | 25°                                                                                                                             |
| Beam angle (1/2 peak):  | 25°                                                                                                                             |
| Beam angle (1/10 peak): | 46°                                                                                                                             |
| Housing color:          | Black                                                                                                                           |
| Dimensions:             | Width: 35.8 cm<br>Depth: 17.4 cm<br>Height: 22.3 cm                                                                             |
| Weight:                 | 7.05 kg                                                                                                                         |

### Scope of delivery: