# EUROLITE LED PAR-20 3CT sil

LED spotlight with three adjustable color temperatures and high color rendering index

**Art. No.: 41607031**

GTIN: 4026397692082











## Features:

- Dimmable
- 1 LED 16 W COB (chip-on-board) 2in1 CW/WW
- Dimmer electronic
- The device is cooled by passive convection cooling
- Control via quick select potentiometer for brightness and color temperature
- Flicker-free
- With a beam angle of 25°
- Direct color temperature selection for 3 preset values
- Very high color rendering index (CRI)
- With mounting bracket
- Available in various colors
- For application areas such as: Clubs/dancing school; decoration; Trade fair and shop fitting; party room; restaurants, bars and hotels; advertisement/Shop window
- Silent operation
- Application possibility: Suspended; on stand

## Logistic

EAN / GTIN: 4026397692082
Weight: 0,57 kg
Length: 0.10 m
Width: 0.10 m
Heigth: 0.24 m

## Technical specifications:

| | |
|---|---|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | Max. 12 W |
| Protection class: | Protection class I |
| Power connection: | Fixed power supply cord with safety plug |
| Cable length: | Approx. 0.4 m |

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

| | |
|---|---|
| Lamp type: | LED lamp |
| Lamp specification: | Dimmable |
| LED type: | 1 x 16 W COB (chip-on-board) 2in1 CW/WW |
| Cooling: | Passive convection cooling |
| Control: | Quick select potentiometer for brightness and color temperature |
| Projection: | Flicker-free |
| Beam angle: | 25° |
| Beam angle (1/2 peak): | 25° |
| Beam angle (1/10 peak): | 50° |
| Color temperature: | 3000K; 4000K; 5000K |
| Color rendering index (CRI): | 90 Ra |
| Illuminance in Lux (lx): | 3000 K 1m: 2078 lx, 3m: 266 lx, 6m: 74 lx<br>4000 K 1m: 2427 lx, 3m: 299 lx, 6m: 80 lx<br>5000 K 1m: 2593 lx, 3m: 322 lx, 6m: 87 lx |
| Lamp life: | 15000 h |
| Luminous flux: | 800 lm |
| Housing color: | Silver |
| Housing shape: | PAR-20 spot |
| Attachment system: | Mounting bracket |
| Material: | Aluminum |
| Slot for spot length: | 8.6 cm x  8.6 cm |
| Dimensions: | Length: 19.2 cm<br>Width: 11.5 cm<br>Height: 16.0 cm |
| Weight: | 0.52 kg |
| Noise classification: | Class 0 (no noise at all) |
| Energy efficiency class (A - G): | G |
| EPREL-Nr: | 1269732 |
| Diameter mounting holes: | 2 x Ø10mm |
| Material: | Aluminum casting, 3 mm |
| Dimensions: | Width: 9.4 cm<br>Depth: 2 cm<br>Height: 12.4 cm |
| Shape: | Octagonal |
| Material: | Aluminum |
| Dimensions: | Width: 8.3 cm<br>Height: 8.3 cm<br>Diameter: Ø 6.1 cm |

## Scope of delivery:

1 x spotlight
1 x filter frame
1 x user manual

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.