

EUROLITE LED PAR-30 3CT sil

LED spotlight with three adjustable color temperatures and high color rendering index

Art. No.: 41607051

GTIN: 4026397692129



Features:

- Dimmable
- 1 LED 16 W COB (chip-on-board) 2in1 CW/WW
- Dimmer electronic
- The device is cooled by passive convection cooling
- Control via quick select potentiometer for brightness and color temperature
- Flicker-free
- With a beam angle of 20°
- Direct color temperature selection for 3 preset values
- Very high color rendering index (CRI)
- With mounting bracket
- Available in various colors
- Silent operation
- For application areas such as: Clubs/dancing school; decoration; Trade fair and shop fitting; party room; restaurants, bars and hotels; advertisement/Shop window
- Application possibility: Suspended; on stand

Logistic

EAN / GTIN: 4026397692129

Weight: 0,87 kg

Length: 0.14 m

Width: 0.14 m

Height: 0.27 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
---------------	------------------------

Power consumption:	18 W
--------------------	------

Protection class:	Protection class I
-------------------	--------------------

Power connection:	Fixed power supply cord with safety plug
-------------------	--

Cable length:	Approx. 0.4 m
---------------	---------------

Lamp type:	LED lamp
Lamp specification:	Dimmable
LED type:	1 x 16 W COB (chip-on-board) 2in1 CW/WW
Cooling:	Passive convection cooling
Control:	Quick select potentiometer for brightness and color temperature
Projection:	Flicker-free
Beam angle:	20°
Beam angle (1/2 peak):	20°
Beam angle (1/10 peak):	35°
Color temperature:	3000K; 4000K; 5000K
Color rendering index (CRI):	90 Ra
Illuminance in Lux (lx):	3000 K 1m: 4760 lx, 3m: 606 lx, 6m: 160 lx 4000 K 1m: 5248 lx, 3m: 631 lx, 6m: 175 lx 5000 K 1m: 5754 lx, 3m: 713 lx, 6m: 191 lx
Lamp life:	15000 h
Luminous flux:	1300 lm
Housing color:	Silver
Attachment system:	Mounting bracket
Material:	Aluminum
Slot for spot length:	12.8 cm x 12.8 cm
Dimensions:	Length: 24 cm Width: 14.7 cm Height: 20 cm
Weight:	0.79 kg
Noise classification:	Class 0 (no noise at all)
Energy efficiency class (A - G):	G
EPREL-Nr:	1269739
Diameter mounting holes:	2 x Ø10mm
Material:	Aluminum casting, 3 mm
Dimensions:	Width: 13 cm Depth: 2 cm Height: 13 cm
Shape:	Octagonal
Material:	Aluminum, 0.8 mm
Dimensions:	Width: 12.6 cm Height: 12.6 cm Diameter: Ø 9.4 cm

Scope of delivery:

1 x spotlight
1 x filter frame
1 x user manual