

## EUROLITE AKKU Flat Light 3 sil

Flat spotlight with 3 x 8 W RGBW LED, QuickDMX transceiver and bracket

Art. No.: 41700015

GTIN: 4026397630015



**The article is no longer in our assortment.**

### Description:

Flat headlight with 3x8 W RGBW LED, Quick DMX transceiver & bracket

The flat spotlight EUROLITE AKKU Flat Light 3 is wireless, flexible and versatile. It is equipped with three powerful 8-watt LEDs (4in1) in red, green, blue and white. If you are looking for a spotlight that does not take up much space and is suitable for use on stages, in discotheques, theatres, bars or even for mobile use, the AKKU Flat Light 3 is the perfect choice.

With an operating time of up to 16 hours with the built-in rechargeable battery, the spotlight is ideal for mobile use.

The compact and powerful spotlight is housed in an elegant housing. The angle of inclination can be adjusted manually via the bracket.

In addition to static colors with infinitely variable RGBW color mixing, you can also use internal programs and a strobe effect with variable speed. The dimmer with adjustable dimmer speed and the music control offer you further possibilities.

You can control the Flat Light 3 via DMX with master/slave function, with the supplied infrared remote control, in stand-alone mode and via the integrated QuickDMX radio transmitter/receiver for wireless transmission of DMX512 signals.

Addressing and setting can also be conveniently done via the touch-sensitive control board and LCD.

In addition, the Flat Light 3 is equipped with a Kensington security connector, with which you can protect your device against theft.

### Logistic

EAN / GTIN: 4026397630015

Weight: 1,83 kg

Length: 0.27 m

Width: 0.20 m

Height: 0.11 m

## Features:

- Integrated QuickDMX transceiver for wireless DMX control
- Elegant housing for indoor use
- Cordless, flexible and versatile
- Battery operation up to 16h depending on program used
- Integrated automatic charging of the battery and status indicator
- 3 LEDs 8 W SMD 9080 4in1 RGBW (homogenous color mix)
- Dimmer curves with adjustable response; color blend stepless; color change adjustable; colors preset; Dimmer electronic
- Strobe effect
- Can be operated in 3; 4; 6; 8; 10 CH mode
- The device is cooled by passive convection cooling
- Control via stand-alone; QuickDMX; sound to light via microphone; IR remote control
- Flicker-free
- With a beam angle of 12°
- With mounting bracket
- Various versions available
- With a KENSINGTON LOCK theft protection
- For application areas such as: Small rental; wedding/gala/events
- Silent operation

## Technical specifications:

|                         |                                                                                                                                                |
|-------------------------|------------------------------------------------------------------------------------------------------------------------------------------------|
| Power supply:           | 100-240 V AC, 50/60 Hz<br>12.6V DC 2500 mA                                                                                                     |
| Pin configuration:      | Inside + / outside -                                                                                                                           |
| Protection class:       | Protection class III                                                                                                                           |
| Power connection:       | Battery/battery pack<br>Mains input via coaxial power connector (M)<br>mounting version power supply cord with Euro<br>plug (provided)         |
| Battery pack type:      | 1 x lithium ion 11.1 V, 5200 mAh, 57.72 Wh                                                                                                     |
| Battery pack:           | Battery operation up to 16h depending on<br>program used<br>Recharging time 4h                                                                 |
| Lamp type:              | LED lamp                                                                                                                                       |
| LED type:               | 3 x 8 W SMD 9080 4in1 RGBW (homogenous<br>color mix)                                                                                           |
| DMX channels:           | 3; 4; 6; 8; 10                                                                                                                                 |
| Cooling:                | Passive convection cooling                                                                                                                     |
| Control:                | Stand-alone; QuickDMX; sound to light via<br>microphone; IR remote control                                                                     |
| Fixtures available for: | Light´J; EASY SHOW 1; LED EASY OPERATOR<br>4x4; LED EASY OPERATOR 4x6; LED EASY<br>OPERATOR DELUXE; Light Captain; EASY<br>SHOW 2; EASY SHOW 3 |
| Projection:             | Flicker-free                                                                                                                                   |
| Carrier frequency:      | 2.4 GHz                                                                                                                                        |
| Beam angle:             | 12°                                                                                                                                            |
| Beam angle (1/2 peak):  | 12°                                                                                                                                            |
| Beam angle (1/10 peak): | 30°                                                                                                                                            |
| Housing color:          | Silver                                                                                                                                         |
| Attachment system:      | Mounting bracket                                                                                                                               |

|                       |                                                         |
|-----------------------|---------------------------------------------------------|
| Theft protection:     | KENSINGTON LOCK                                         |
| Dimensions:           | Width: 16.8 cm<br>Depth: 13.8 cm<br>Height: 6.2 cm      |
| Weight:               | 1.62 kg                                                 |
| Noise classification: | Class 0 (no noise at all)                               |
| Battery:              | 1 x button cell 3.0 V CR2032 lithium manganese built-in |

### Scope of delivery:

1 x device  
1 x user manual  
1 x external mains adapter  
1 x remote control  
1 x declaration of conformity  
1 x power cord