

EUROLITE AKKU Flat Light 3 bk

Flat spotlight with 3 x 8 W RGBW LED, QuickDMX transceiver and bracket

Art. No.: 41700016

GTIN: 4026397630022



List price: 272.51 €

incl. 19% VAT.

Description:

Flat headlight with 3x8 W RGBW LED, Quick DMX transceiver & bracket

The flat spotlight EUROLITE AKKU Flat Light 3 is wireless, flexible and versatile. It is equipped with three powerful 8-watt LEDs (4in1) in red, green, blue and white. If you are looking for a spotlight that does not take up much space and is suitable for use on stages, in discotheques, theatres, bars or even for mobile use, the AKKU Flat Light 3 is the perfect choice.

With an operating time of up to 16 hours with the built-in rechargeable battery, the spotlight is ideal for mobile use.

The compact and powerful spotlight is housed in an elegant housing. The angle of inclination can be adjusted manually via the bracket.

In addition to static colors with infinitely variable RGBW color mixing, you can also use internal programs and a strobe effect with variable speed. The dimmer with adjustable dimmer speed and the music control offer you further possibilities.

You can control the Flat Light 3 via DMX with master/slave function, with the supplied infrared remote control, in stand-alone mode and via the integrated QuickDMX radio transmitter/receiver for wireless transmission of DMX512 signals.

Addressing and setting can also be conveniently done via the touch-sensitive control board and LCD.

In addition, the Flat Light 3 is equipped with a Kensington security connector, with which you can protect your device against theft.

Logistic

EAN / GTIN: 4026397630022

Weight: 1,83 kg

Length: 0.27 m

Width: 0.20 m

Height: 0.11 m

Features:

- Integrated QuickDMX transceiver for wireless DMX control
- Elegant housing for indoor use
- Cordless, flexible and versatile
- Battery operation up to 16h depending on program used
- Integrated automatic charging of the battery and status indicator
- 3 LEDs 8 W SMD 9080 4in1 RGBW (homogenous color mix)
- Dimmer electronic; color change adjustable; color fade adjustable; Dimmer speed (step response) adjustable
- Strobe effect
- Direct color selection for 30 preset colors
- Can be operated in 3; 4; 6; 8; 10 CH mode
- The device is cooled by passive convection cooling
- Control via stand-alone; QuickDMX; IR remote control; sound to light via microphone
- Flicker-free
- With a beam angle of 12°
- With mounting bracket
- OLED display
- Various versions available
- With a KENSINGTON LOCK theft protection
- For application areas such as: Decoration; wedding/gala/events; mobile djs / entertainer; party room; restaurants, bars and hotels
- Application possibility: Standing
- Silent operation

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz 12.6V DC 2500 mA
Protection class:	Protection class III
Power connection:	Battery/battery pack Mains input via coaxial power connector (M) mounting version power supply cord with Euro plug (provided)
Battery pack type:	2 x lithium ion 11.1 V, 2600 mAh, 28.86 Wh
Battery pack:	Battery operation up to 16h depending on program used Recharging time 4h
Lamp type:	LED lamp
LED type:	3 x 8 W SMD 9080 4in1 RGBW (homogenous color mix)
DMX channels:	3; 4; 6; 8; 10
Cooling:	Passive convection cooling
Control:	Stand-alone; QuickDMX; IR remote control; sound to light via microphone
Fixtures available for:	Light J; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
Carrier frequency:	2.4 GHz
Beam angle:	12°
Beam angle (1/2 peak):	12°
Beam angle (1/10 peak):	30°
Housing color:	Black

Attachment system:	Mounting bracket
Display type:	OLED display
Theft protection:	KENSINGTON LOCK
Dimensions:	Width: 16.8 cm Depth: 13.8 cm Height: 6.2 cm
Weight:	1.62 kg
Noise classification:	Class 0 (no noise at all)
Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in

Scope of delivery:

- 1 x spotlight
- 1 x user manual
- 1 x external mains adapter
- 1 x remote control
- 1 x battery
- 1 x declaration of conformity