

EUROLITE AKKU Bar-6 Entry QCL RGBW Bar

Battery-powered light effect bar with RGBW LEDs and IR remote control

Art. No.: 41700101

GTIN: 4026397689662



List price: 208.25 €

incl. 19% VAT.

Features:

- Cordless, flexible and versatile
- 6 LEDs 8 W SMD 9080 4in1 RGBW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Energy-saving mode
- Strobe effect
- Integrated show programs
- Direct color selection for 19 preset colors
- Can be operated in 3; 4; 6; 8 CH mode
- The device is cooled by passive convection cooling
- Control via stand-alone; IR remote control; DMX; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- With a beam angle of 18°
- With mounting bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; decoration; wedding/gala/events; mobile djs / entertainer; party room; restaurants, bars and hotels
- Silent operation
- Application possibility: Standing; suspended

Logistic

EAN / GTIN: 4026397689662

Weight: 3,05 kg

Length: 0.56 m

Width: 0.15 m

Height: 0.17 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	IEC connector (F) mounting version
Fuse:	T 0.5 A fuse replaceable
Battery pack type:	1 x lithium ion 22.2 V, 2200 mAh, 48.84 Wh
Battery pack:	Recharging time 3h
Lamp type:	LED lamp
LED type:	6 x 8 W SMD 9080 4in1 RGBW (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	3; 4; 4; 6; 8
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; IR remote control; DMX; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Light J; Colorchief
Projection:	Flicker-free
Beam angle:	18°
Beam angle (1/2 peak):	18°
Beam angle (1/10 peak):	35°
Housing color:	Black
Attachment system:	2x mounting bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Length: 54.5 cm Depth: 13.8 cm Height: 15.7 cm
Weight:	2.76 kg
Noise classification:	Class 0 (no noise at all)
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in

Scope of delivery:

1 x device
1 x user manual
1 x power cord
1 x remote control
1 x battery
2 x mounting bracket
2 x knurled screw
2 x washer