

EUROLITE AKKU Bar-6 Glow QCL Flex QuickDMX

Tiltable battery-powered LED bar and mood light with 4in1 LEDs and QuickDMX

Art. No.: 41700120

GTIN: 4026397635850



Features:

- 100° tiltable bar with 6 high-power 8 W RGBW LEDs (4in1) and removable frost filter
- Mood light with milky front screen provides a pleasantly soft light with 30 SMD RGBW LEDs (4in1)
- Integrated QuickDMX transceiver for wireless DMX control
- Cordless, flexible and versatile
- Battery operation up to 13h depending on program used
- Integrated automatic charging of the battery and status indicator
- 30 LEDs 0.25 W SMD 5050 4in1 RGBW (homogenous color mix)
- 6 LEDs 8 W SMD 9080 4in1 RGBW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) adjustable
- Atmospheric effect
- Integrated show programs
- Direct color selection for 30 preset colors
- Can be operated in 3; 7; 8; 9; 11 CH mode
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; QuickDMX; IR remote control; sound to light via microphone; master/slave function
- Flicker-free
- With a beam angle of 15°
- Multicolor LCD display
- With a KENSINGTON LOCK theft protection
- For application areas such as: Clubs/dancing school; decoration; wedding/gala/events; mobile djs / entertainer; party room; restaurants, bars and hotels; advertisement/Shop window
- Silent operation
- Application possibility: Standing; suspended; on stand

Logistic

EAN / GTIN: 4026397635850

Weight: 3,50 kg

Length: 0.55 m

Width: 0.17 m

Height: 0.14 m

knurled screw

- M6 thread

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Protection class:	Protection class I
Power connection:	Battery/battery pack Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Battery pack type:	1 x lithium ion 11.1 V, 10400 mAh, 115.44 Wh
Battery pack:	Battery operation up to 13h depending on program used Recharging time 4h
Lamp type:	LED lamp
LED type:	30 x 0.25 W SMD 5050 4in1 RGBW (homogenous color mix) 6 x 8 W SMD 9080 4in1 RGBW (homogenous color mix)
DMX channels:	3; 7; 8; 9; 11
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; QuickDMX; IR remote control; sound to light via microphone; master/slave function
Fixtures available for:	LED PC-Control 512; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
Carrier frequency:	2.4 GHz
Beam angle:	15°
Beam angle (1/2 peak):	15°
Beam angle (1/10 peak):	30°
Housing color:	Black
Display type:	Multicolor LCD display
Material:	Plastic; metal
Theft protection:	KENSINGTON LOCK
Dimensions:	Length: 41.1 cm Depth: 9.5 cm Height: 10.5 cm
Weight:	2.80 kg
Noise classification:	Class 0 (no noise at all)
Cable construction:	3 x 1.0 mm ² H05VV-F
Diameter mounting holes:	2 x Ø4mm
Material:	Plastic, 2 mm
Dimensions:	Length: 33.5 cm Width: 3.9 cm

Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in
Diameter mounting holes:	1 x Ø11mm; 2 x Ø6mm
Material:	Metal, 2 mm
Dimensions:	Length: 11.7 cm Width: 2.5 cm Height: 2.7 cm
Weight:	0.048 kg
Material:	Metal
Thread:	M6 thread x 11 mm
Diameter mounting holes:	Ø10mm
Material:	Metal, 0.5 mm
Dimensions:	Diameter: Ø 1.2 cm

Scope of delivery:

- 1 x device
- 1 x power cord
- 1 x frost filter
- 1 x remote control
- 1 x battery
- 1 x omega bracket
- 4 x knurled screw
- 4 x washer
- 1 x user manual
- 1 x declaration of conformity