

EUROLITE AKKU Table Light 2 RGB+WW

Rechargeable outdoor lamp with warm white light and 8 RGB colors

Art. No.: 41700330

GTIN: 4026397703658



Features:

- Two white light modes
- Comfortable control via pull switch
- Cordless, flexible and versatile
- Battery operation up to 40h
- 4 LEDs SMD 5050 3in1 RGB (homogenous color mix)
- 9 LEDs 0.2 W SMD 2835 warm white (WW)
- Color selection manual; color fade stepless
- The device is cooled by passive convection cooling
- Control via on/off switch on device
- Good color rendering index (CRI)
- Suitable for outdoor use IP44
- For application areas such as: Wedding/gala/events; party room; restaurants, bars and hotels; decoration
- Silent operation
- Application possibility: Standing

Logistic

EAN / GTIN: 4026397703658

Weight: 0,83 kg

Length: 0.15 m

Width: 0.15 m

Height: 0.17 m

Technical specifications:

Power supply:	3.7V DC
---------------	---------

IP classification:	IP44
--------------------	------

Protection class:	Protection class III
-------------------	----------------------

Nominal wattage:	1.8 W
------------------	-------

Power connection:	Mains input via USB C (W) mounting version power supply cord for USB A mains connection (provided)
Battery pack type:	2 x lithium ion 3.7 V, 1800 mAh, 6.66 Wh
Battery pack:	Battery operation up to 40h
Lamp type:	LED lamp
LED type:	4 x SMD 5050 3in1 RGB (homogenous color mix) 9 x 0.2 W SMD 2835 warm white (WW)
Cooling:	Passive convection cooling
Control:	On/off switch on device
Color temperature:	3000K
Color rendering index (CRI):	83 Ra
Luminous flux:	200 lm
Housing color:	Semi-transparent; white
Status LED:	Power, charge status indicator
Dimensions:	Height: 26.5 cm Diameter: Ø 15.3 cm
Weight:	0.72 kg
Noise classification:	Class 0 (no noise at all)
Energy efficiency class (A - G):	F
EPREL-Nr:	1142042
Cable length:	Approx. 0.8 m
Material:	Metal
Dimensions:	Height: 12 cm Diameter: Ø 1.9 cm
Material:	Metal, 2.5 mm
Dimensions:	Diameter: Ø 15 cm

Scope of delivery:

1 x light effect
 1 x USB cable
 1 x stand
 1 x plate
 1 x user manual