

## EUROLITE AKKU B-40 Laser Beam Effect AIR white

Art. No.: 41700341

Battery-powered LED beam effect with RGBW colors, RG laser, AirW wireless system (2.4 GHz) and RF remote control

GTIN: 4026397741162



### Features:

- Integrated AirW radio transceiver for wireless master/slave operation
- Adaptive frequency hopping ensures interference-free operation in the 2.4 GHz band
- 2 laser diodes project hundreds of red and green laser beams
- Cordless, flexible and versatile
- Battery operation up to 11h depending on program used
- Integrated automatic charging of the battery
- 5 LEDs 8 W SMD 9095 4in1 RGBW<BR>3 segments controlled separately
- Dimmer electronic; color selection adjustable; program selection manual; Energy-saving mode adjustable; program speed adjustable; Rotation speed adjustable; Rotation direction adjustable
- Multi beam effect; laser; strobe effect
- Laser class 2M <BR> does not require additional protective measures or appointment of a laser safety officer
- 7 integrated show programs
- Can be operated in 3; 10; 22 CH mode
- Highly efficient air flow from front to rear
- The device is cooled by low-noise cooling fan at the base
- Control via stand-alone; DMX; AirW; sound to light via microphone; master/slave function; wireless remote control; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- With omega bracket
- Monochrome 4 digit 7-segment LED display
- Charge status indicator
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; wedding/gala/events; mobile djs / entertainer; party room; restaurants, bars and hotels; advertisement/Shop window

### Logistic

EAN / GTIN: 4026397741162

Weight: 9,00 kg

Length: 0.40 m

Width: 0.43 m

Height: 0.53 m

- Very quiet working noise
- Application possibility: Standing; suspended
- 3 buttons on the remote control for saving your own settings

#### **remote control**

- Operating range up to 50m in the open air

### **Technical specifications:**

|                         |                                                                                                                                                                                                                          |
|-------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power supply:           | 100-240 V AC, 50/60 Hz                                                                                                                                                                                                   |
| Protection class:       | Protection class I                                                                                                                                                                                                       |
| Power connection:       | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)<br>Battery/battery pack built-in                                                                                        |
| Cable construction:     | 3 x 1.0 mm <sup>2</sup> H05VV-F                                                                                                                                                                                          |
| Power output:           | 1 x IEC connector (F) mounting version Bypass                                                                                                                                                                            |
| Fuse:                   | 5 x 20 mm, T 2 A fuse replaceable                                                                                                                                                                                        |
| Battery pack type:      | 1 x lithium ion 18.5 V, 13000 mAh, 240.5 Wh                                                                                                                                                                              |
| Battery pack:           | Battery operation up to 11h depending on program used<br>Recharging time 7h                                                                                                                                              |
| Lamp type:              | LED lamp                                                                                                                                                                                                                 |
| LED type:               | 5 x 8 W SMD 9095 4in1 RGBW                                                                                                                                                                                               |
| Flash rate:             | 1 - 20 Hz                                                                                                                                                                                                                |
| Laser class:            | 2M                                                                                                                                                                                                                       |
| Laser color:            | R/G                                                                                                                                                                                                                      |
| Laser module:           | Red (R) 100 mW 650nm<br>Green (G) 40 mW 532nm                                                                                                                                                                            |
| DMX channels:           | 3; 10; 22                                                                                                                                                                                                                |
| DMX input:              | 1 x 3-pin XLR (M) mounting version                                                                                                                                                                                       |
| DMX output:             | 1 x 3-pin XLR (F) mounting version Bypass                                                                                                                                                                                |
| Cooling:                | 1 x low-noise cooling fan at the base, air flow from front to rear                                                                                                                                                       |
| Control:                | Stand-alone; DMX; AirW; sound to light via microphone; master/slave function; wireless remote control; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) |
| Fixtures available for: | Light' J; Light Captain                                                                                                                                                                                                  |
| Projection:             | Flicker-free                                                                                                                                                                                                             |
| DMX fail mode:          | Blackout; hold; auto; full on                                                                                                                                                                                            |
| Housing color:          | White                                                                                                                                                                                                                    |
| Attachment system:      | Omega bracket                                                                                                                                                                                                            |
| Display type:           | Monochrome 4 digit 7-segment LED display                                                                                                                                                                                 |
| Display reading:        | Charge status indicator                                                                                                                                                                                                  |
| Status LED:             | Power, charge status indicator                                                                                                                                                                                           |
| USB port:               | 1 x type A                                                                                                                                                                                                               |
| Material:               | Metal, painted                                                                                                                                                                                                           |
| Dimensions:             | Length: 32 cm                                                                                                                                                                                                            |

|                       |                                                                        |
|-----------------------|------------------------------------------------------------------------|
|                       | Width: 26 cm<br>Height: 39 cm                                          |
| Weight:               | 7.00 kg                                                                |
| Noise classification: | Class 1 (very slight noise, suitable for noise-sensitive environments) |
| Material thickness:   | 3 mm                                                                   |
| Battery:              | 1 x 12 V 23AE alkaline manganese built-in                              |
| Range:                | Range up to 50m in the open air                                        |
| Carrier frequency:    | 433.92 MHz                                                             |

### Scope of delivery:

1 x light effect  
1 x power cord  
1 x omega bracket  
1 x user manual  
1 x remote control  
4 x screw  
4 x washer  
1 x declaration of conformity  
1 x battery