

EUROLITE AKKU PT-100/32 Pixel DMX Tube

Battery-powered and DMX-controllable pixel tube with RGB color mixing

Art. No.: 41700350

GTIN: 4026397693973



List price: 296.31 €

incl. 19% VAT.

Features:

- Rugged metal housing
- Cordless, flexible and versatile
- Battery operation up to 9h depending on program used
- 96 LEDs SMD 5050 3in1 RGB (homogenous color mix)
32 segments controlled separately
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- 12 integrated show programs
- Direct color selection for 17 preset colors
- Can be operated in 3; 5; 8; 48; 96 CH mode
- The device is cooled by passive convection cooling
- Control via stand-alone; IR remote control; DMX; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- 4 digit 7-segment LED display
- For application areas such as: Architecture; stage; decoration; wedding/gala/events; mobile djs / entertainer; party room; restaurants, bars and hotels
- Silent operation
- Application possibility: Standing; suspended; wall mounting

Logistic

EAN / GTIN: 4026397693973

Weight: 3,00 kg

Length: 1.05 m

Width: 0.10 m

Height: 0.20 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz
13V DC

Pin configuration: Inside + / outside -

Protection class:	Protection class III
Power connection:	Mains input via coaxial power connector (M) mounting version power supply cord with AC adapter (provided) Battery/battery pack
Battery pack type:	1 x lithium ion 11.1 V, 4400 mAh, 48.84 Wh
Battery pack:	Battery operation up to 9h depending on program used Recharging time 1.5h
Lamp type:	LED lamp
LED type:	96 x SMD 5050 3in1 RGB (homogenous color mix)
Flash rate:	0.2 - 10 Hz
DMX channels:	3; 5; 8; 48; 96
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; IR remote control; DMX; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W- DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	Light Captain; Light J
PWM frequency:	2000 Hz
Housing color:	Black
Display type:	4 digit 7-segment LED display
Dimensions:	Width: 5 cm Depth: 12.7 cm Height: 100 cm
Weight:	2.50 kg
Noise classification:	Class 0 (no noise at all)
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in

Scope of delivery:

1 x device
 1 x user manual
 1 x external mains adapter
 1 x stand
 1 x remote control
 1 x battery