

## EUROLITE AKKU PT-100/32 Pixel DMX Tube

Battery-powered and DMX-controllable pixel tube with RGB color mixing

Art. No.: 41700350

GTIN: 4026397693973



### Features:

- Rugged metal housing
- Cordless, flexible and versatile
- Battery operation up to 9h depending on program used
- 96 LEDs SMD 5050 3in1 RGB (homogenous color mix) <BR>32 segments controlled separately
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- 12 integrated show programs
- Direct color selection for 17 preset colors
- Can be operated in 3; 5; 8; 48; 96 CH mode
- The device is cooled by passive convection cooling
- Control via stand-alone; IR remote control; DMX; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- 4 digit 7-segment LED display
- For application areas such as: Architecture; stage; decoration; wedding/gala/events; mobile djs / entertainer; party room; restaurants, bars and hotels
- Silent operation
- Application possibility: Standing; suspended; wall mounting

### Logistic

EAN / GTIN: 4026397693973

Weight: 3,00 kg

Length: 1.05 m

Width: 0.10 m

Height: 0.20 m

### Technical specifications:

|               |                                  |
|---------------|----------------------------------|
| Power supply: | 100-240 V AC, 50/60 Hz<br>13V DC |
|---------------|----------------------------------|

|                    |                      |
|--------------------|----------------------|
| Pin configuration: | Inside + / outside - |
|--------------------|----------------------|

|                         |                                                                                                                                                                                                                           |
|-------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Protection class:       | Protection class III                                                                                                                                                                                                      |
| Power connection:       | Mains input via coaxial power connector (M)<br>mounting version power supply cord with AC<br>adapter (provided)<br><br>Battery/battery pack                                                                               |
| Battery pack type:      | 1 x lithium ion 11.1 V, 4400 mAh, 48.84 Wh                                                                                                                                                                                |
| Battery pack:           | Battery operation up to 9h depending on program<br>used<br><br>Recharging time 1.5h                                                                                                                                       |
| Lamp type:              | LED lamp                                                                                                                                                                                                                  |
| LED type:               | 96 x SMD 5050 3in1 RGB (homogenous color<br>mix)                                                                                                                                                                          |
| Flash rate:             | 0.2 - 10 Hz                                                                                                                                                                                                               |
| DMX channels:           | 3; 5; 8; 48; 96                                                                                                                                                                                                           |
| DMX input:              | 3-pin XLR (M) mounting version                                                                                                                                                                                            |
| DMX output:             | 3-pin XLR (F) mounting version                                                                                                                                                                                            |
| Cooling:                | Passive convection cooling                                                                                                                                                                                                |
| Control:                | Stand-alone; IR remote control; DMX;<br>master/slave function; sound to light via<br>microphone; QuickDMX via USB (optional); W-<br>DMX by wireless solution via USB (optional);<br>CRMX by LumenRadio via USB (optional) |
| Fixtures available for: | Light Captain; Light´J                                                                                                                                                                                                    |
| PWM frequency:          | 2000 Hz                                                                                                                                                                                                                   |
| Housing color:          | Black                                                                                                                                                                                                                     |
| Display type:           | 4 digit 7-segment LED display                                                                                                                                                                                             |
| Dimensions:             | Width: 5 cm<br>Depth: 12.7 cm<br>Height: 100 cm                                                                                                                                                                           |
| Weight:                 | 2.50 kg                                                                                                                                                                                                                   |
| Noise classification:   | Class 0 (no noise at all)                                                                                                                                                                                                 |
| Battery:                | 1 x button cell 3.0 V CR2025 lithium manganese<br>built-in                                                                                                                                                                |

## Scope of delivery:

1 x device  
 1 x user manual  
 1 x external mains adapter  
 1 x stand  
 1 x remote control  
 1 x battery