

EUROLITE AKKU UP-7 QCL Spot QuickDMX

Uplight with 7 x 8 W 4in1 LED, QuickDMX transceiver, frost filter and IR remote control

Art. No.: 41700544

GTIN: 4026397670387



Features:

- Integrated QuickDMX transceiver for wireless DMX control
- Additional frost filter provides a wide, soft and homogeneous light
- Sturdy metal housing with handle and folding foot for angled placement
- Cordless, flexible and versatile
- Battery operation up to 17h depending on program used
- Integrated automatic charging of the battery and status indicator
- 7 LEDs 8 W high-power 4in1 RGBW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) adjustable; white balance adjustable
- Strobe effect
- 36 integrated show programs
- Direct color selection for 15 preset colors
- Can be operated in 3; 4; 6; 8; 11 CH mode
- The device is cooled by passive convection cooling
- Control via DMX; stand-alone; IR remote control; master/slave function; sound to light via microphone; QuickDMX
- Flicker-free
- With a beam angle of 9°
- Monochrome OLED display
- Rubber feet
- Mains input and output for power linking up to 8 units
- With a KENSINGTON LOCK theft protection
- For application areas such as: Wedding/gala/events; mobile djs / entertainer; rental
- Silent operation
- Application possibility: Standing

Logistic

EAN / GTIN: 4026397670387

Weight: 4,00 kg

Length: 0.21 m

Width: 0.21 m

Height: 0.23 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	70 W
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided) Battery/battery pack built-in
Cable length:	Approx. 1.2 m
Power output:	1 x P-Con (grey), mounting version
Battery pack type:	1 x lithium ion 25.9 V, 7800 mAh, 202.02 Wh
Battery pack:	Battery operation up to 17h depending on program used Recharging time 3.5h
Lamp type:	LED lamp
LED type:	7 x 8 W high-power 4in1 RGBW (homogenous color mix)
Flash rate:	1 - 23 Hz
DMX channels:	3; 4; 6; 8; 11
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	DMX; stand-alone; IR remote control; master/slave function; sound to light via microphone; QuickDMX
Fixtures available for:	EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light J; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
Carrier frequency:	2.4 GHz
Beam angle:	9°
Beam angle (1/2 peak):	9°
Beam angle (1/10 peak):	18°
Housing color:	Black
Display type:	Monochrome OLED display
Transport aid:	Rubber feet
Theft protection:	KENSINGTON LOCK
Dimensions:	Width: 13.8 cm Depth: 16.7 cm Height: 18.9 cm
Weight:	3.60 kg
Noise classification:	Class 0 (no noise at all)
Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in

Scope of delivery:

1 x device
1 x power cord
1 x remote control
1 x battery
1 x frost filter
2 x knurled screw
1 x declaration of conformity
1 x user manual