

EUROLITE AKKU UP-4 QCL Spot WDMX

Uplight with 4 x 8 W 4in1 LED & wireless DMX receiver (Wireless Solution)

Art. No.: 41700555

GTIN: 4026397531893



The article is no longer in our assortment.

Features:

- Compact and bright
 - Equipped with 4 x 8 W QCL LED in red, green, blue and white
 - With integrated wireless receiver for WDMX operation (Wireless Solution - made in Sweden)
 - Operation via mains connection or built-in rechargeable lithium-ion battery with up to 8.5 hours operating time
 - Integrated automatic charging of the battery with indicator
 - Controllable via EUROLITE IR-7 remote control; included in the delivery
 - With integrated folding foot for angled placement by floor installation
 - DMX-controlled operation or stand-alone operation with Master/Slave function
 - 4, 6 or 10 DMX channels selectable
 - Functions: static colors, stepless RGBW color mixture, internal programs, dimmer, strobe effect with variable speed, sound-control
 - Dimmer speed (step response) adjustable
 - Adjustable microphone sensitivity
 - Addressing via control panel with 4-digit LED display
 - Switch-mode power supply for operation between 100 and 240 volts
 - Ready for connection via included power cable with safety power plug
 - Feed-through output allows to power up to 8 devices
 - 4 LEDs 8 W SMD 9080 4in1 RGBW (homogenous color mix)
 - Can be operated in 4; 6; 10 CH mode
 - The device is cooled by passive convection cooling
 - Control via DMX; stand-alone; W-DMX by wireless solution; sound to light via microphone
 - Flicker-free
 - With a beam angle of 13°
- device**
- Cordless, flexible and versatile

Logistic

EAN / GTIN: 4026397531893

Weight: 3,20 kg

Length: 0.23 m

Width: 0.20 m

Height: 0.27 m

- Battery operation up to 8.5h

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	45 W
Power connection:	Battery/battery pack Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Lamp type:	LED lamp
LED type:	4 x 8 W SMD 9080 4in1 RGBW (homogenous color mix)
DMX channels:	4; 6; 10
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	DMX; stand-alone; W-DMX by wireless solution; sound to light via microphone
Fixtures available for:	Light´J; LED PC-Control 512
Projection:	Flicker-free
Carrier frequency:	2.4 GHz
Beam angle:	13°
Beam angle (1/2 peak):	13°
Housing color:	Black
Dimensions:	Width: 13.8 cm Depth: 14.5 cm Height: 19.1 cm
Weight:	2.90 kg
Battery pack type:	1 x lithium ion 14.8 V, 6600 mAh, 97.68 Wh
Battery pack:	Battery operation up to 8.5h Recharging time 5h
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in

Scope of delivery:

- 1 x device
- 1 x remote control