

EUROLITE AKKU UP-4 HCL Spot WDMX bk

LED Uplight with 4 x 12 W 6in1 LED & wireless DMX receiver (Wireless Solution)

Art. No.: 41700560

GTIN: 4026397539127



The article is no longer in our assortment.

Features:

- Compact and bright
 - Equipped with 4 x 12 W HCL (hexacolor LED) in red, green, blue, amber, white and UV
 - With integrated wireless receiver for WDMX operation (Wireless Solution - made in Sweden)
 - Operation via mains connection or built-in rechargeable lithium-ion battery with up to 8.5 hours operating time
 - Integrated automatic charging of the battery with indicator
 - Controllable via EUROLITE IR-7 remote control; included in the delivery
 - With integrated folding foot for angled placement by floor installation
 - DMX-controlled operation or stand-alone operation with Master/Slave function
 - 6, 8 or 12 DMX channels selectable
 - Functions: static colors, stepless RGBAW+UV color mixture, internal programs, dimmer, strobe effect with variable speed, sound-control
 - Dimmer speed (step response) adjustable
 - Adjustable microphone sensitivity
 - Addressing via control panel with 4-digit LED display
 - Switch-mode power supply for operation between 100 and 240 volts
 - Ready for connection via included power cable with safety power plug
 - Feed-through output allows to power up to 8 devices
 - DMX control via any standard DMX controller
 - Available in 2 housing colors: black and white
 - The device is cooled by passive convection cooling
 - Control via stand-alone; W-DMX by wireless solution; IR remote control
 - Flicker-free
 - With a beam angle of 22°
- device**
- Cordless, flexible and versatile

Logistic

EAN / GTIN: 4026397539127

Weight: 3,31 kg

Length: 0.22 m

Width: 0.20 m

Height: 0.25 m

- Battery operation up to 8.5h depending on program used

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	37 W
Lamp type:	LED lamp
Cooling:	Passive convection cooling
Control:	Stand-alone; W-DMX by wireless solution; IR remote control
Fixtures available for:	Light´ J; LED PC-Control 512; Light Captain
Projection:	Flicker-free
Beam angle:	22°
Beam angle (1/2 peak):	22°
Beam angle (1/10 peak):	33°
Housing color:	Black
Dimensions:	Width: 13.8 cm Depth: 14.5 cm Height: 19.1 cm
Weight:	2.91 kg
Battery pack type:	1 x lithium ion 14.8 V, 6600 mAh, 97.68 Wh
Battery pack:	Battery operation up to 8.5h depending on program used Recharging time 4.5h
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Battery pack type:	Li-ion 14.8 V, 6600 mAh (97.68 Wh)
Battery operation:	8.5 hours
Recharging time:	4.5 hours
Battery remote control:	CR2025 button cell 3 V
DMX channels:	6/8/12
DMX connection:	3-pin XLR
Sound-control:	via built-in microphone
Wireless signal transmission:	2.4 GHz (ISM)
LED type:	12 W HCL
LED number:	4
Beam angle:	22°
Dimensions (L x W x H):	145 x 138 x 191 mm

Scope of delivery:

- 1 x device
- 1 x remote control