

EUROLITE AKKU IP UP-4 QCL Spot WDMX Tour Set

Flightcase set, 6 AKKU UP-4 Chrome IP 65 with 4 x 10 W LED, with charger

Art. No.: 41700565

GTIN: 4026397604566



The article is no longer in our assortment.

Features:

- Elegant chrome edition with six LED uplights, IR remote control and practical transport case
- Compact and bright
- LED uplights suitable for external use (IP54)
- Every uplight is equipped with 4 x 10 W QCL LED in red, green, blue and white
- With integrated wireless receiver for WDMX operation (Wireless Solution - made in Sweden)
- Operation via built-in rechargeable lithium-ion battery with up to 17 hours operating time
- Integrated automatic charging of the battery with indicator
- Safe storage and recharging in transport case with integrated multi-charger
- Folding foot for angled placement by floor installation
- Hanging as well as standing installation possible
- WDMX-controlled operation or stand-alone operation via Control board and EUROLITE IR-7 remote control
- Functions: static colors, stepless RGBW color mixture, internal programs, dimmer, strobe effect with variable speed, white balance
- Dimmer speed (step response) adjustable
- Addressing and setting via Control Board with four operating buttons and OLED display
- Switch-mode power supply for operation between 100 and 240 volts
- Power connection of the transport case via PowerCon jack and included power cable with safety plug
- DMX control via any standard DMX controller
- 4 LEDs 10 W SMD 5050 4in1 RGBW (homogenous color mix)
- Can be operated in 3; 4; 6; 10 CH mode
- The device is cooled by passive convection cooling
- Control via stand-alone; W-DMX by wireless solution
- Flicker-free
- With a beam angle of 9°

Logistic

EAN / GTIN: 4026397604566

Weight: 48,75 kg

Length: 0.55 m

Width: 0.48 m

Height: 0.55 m

Bulky product

- Suitable for outdoor use IP54
spotlight
- Cordless, flexible and versatile
- Battery operation up to 17h depending on program used

Technical specifications:

Power consumption:	330 W
IP classification:	IP54
Power connection:	Battery/battery pack Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided)
Lamp type:	LED lamp
LED type:	4 x 10 W SMD 5050 4in1 RGBW (homogenous color mix)
DMX channels:	3 (HSV hue/saturation/value); 3 (HSI hue/saturation/intensity); 4; 6; 10
Cooling:	Passive convection cooling
Control:	Stand-alone; W-DMX by wireless solution
Fixtures available for:	Light´J; LED PC-Control 512
Projection:	Flicker-free
Carrier frequency:	2.4 GHz
Beam angle:	9°
Beam angle (1/2 peak):	9°
Beam angle (1/10 peak):	18°
Housing color:	Silver
Dimensions:	Width: 47 cm Depth: 53.7 cm Height: 54 cm
Weight:	48.00 kg
Power supply:	12/24V DC
Battery pack type:	1 x lithium ion 14.8 V, 11000 mAh, 162.8 Wh
Battery pack:	Battery operation up to 17h depending on program used Recharging time 5h
Dimensions:	Height: 20 cm
Weight:	3.8 kg
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Power supply:	100-240 V AC, 50/60 Hz

Scope of delivery:

- 1 x spotlight
- 1 x remote control
- 1 x case