

EUROLITE AKKU UP-4 Entry QCL Spot

Battery-powered uplight with 4 x 8 W 4in1 LED and IR remote control

Art. No.: 41700575

GTIN: 4026397691603



List price: 213.01 €

incl. 19% VAT.

Features:

- Sturdy housing with handle and folding foot for angled placement
- Cordless, flexible and versatile
- Battery operation up to 14h depending on program used
- Integrated automatic charging of the battery and status indicator
- 4 LEDs 8 W SMD 9080 4in1 RGBW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Energy-saving mode
- Strobe effect
- Integrated show programs
- Direct color selection for 17 preset colors
- Can be operated in 3; 4-1; 4; 6; 8 CH mode
- The device is cooled by passive convection cooling
- Control via stand-alone; IR remote control; DMX; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- With a beam angle of 17°
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Decoration; wedding/gala/events; mobile djs / entertainer; restaurants, bars and hotels; rental; advertisement/Shop window
- Silent operation
- Application possibility: Standing

Logistic

EAN / GTIN: 4026397691603

Weight: 2,55 kg

Length: 0.20 m

Width: 0.20 m

Height: 0.23 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	IEC connector (F) mounting version
Fuse:	T 1 A fuse replaceable
Battery pack type:	1 x lithium ion 11.1 V, 4400 mAh, 48.84 Wh
Battery pack:	Battery operation up to 14h depending on program used Recharging time 4h
Lamp type:	LED lamp
LED type:	4 x 8 W SMD 9080 4in1 RGBW (homogenous color mix)
Flash rate:	0.5 - 24 Hz
DMX channels:	3; 4-1; 4; 6; 8
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; IR remote control; DMX; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Light J; Colorchief
Projection:	Flicker-free
PWM frequency:	2900 Hz
Beam angle:	17°
Beam angle (1/2 peak):	17°
Beam angle (1/10 peak):	34°
Housing color:	Black
Attachment system:	M10 thread
Display type:	4 digit 7-segment LED display
Dimensions:	Width: 14.4 cm Depth: 14.4 cm Height: 19.1 cm
Weight:	2.35 kg
Noise classification:	Class 0 (no noise at all)
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in

Scope of delivery:

1 x spotlight
1 x user manual
1 x power cord
1 x remote control

1 x battery