

EUROLITE AKKU Mini IP UP-4 QCL Spot

Mini battery uplight IP65 with RGBW LEDs and IR remote control

Art. No.: 41700615

GTIN: 4026397695694



The article is no longer in our assortment.

Features:

- Cordless, flexible and versatile
- Battery operation up to 9h depending on program used
- Integrated automatic charging of the battery
- 4 LEDs 4 W 4in1 RGBW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable
- Strobe effect
- Direct color selection for 10 preset colors
- The device is cooled by passive convection cooling
- Control via sound to light via microphone; stand-alone; IR remote control
- Flicker-free
- With a beam angle of 19°
- With mounting bracket
- 4 digit 7-segment LED display
- Suitable for outdoor use IP65
- Silent operation

Logistic

EAN / GTIN: 4026397695694

Weight: 1,35 kg

Length: 0.19 m

Width: 0.13 m

Height: 0.12 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz 12.6V 1500 mA
---------------	---

Power consumption:	Max. 30 W
--------------------	-----------

IP classification:	IP65
--------------------	------

Protection class:	Protection class III
-------------------	----------------------

Power connection:	Battery/battery pack Mains input via coaxial power connector (M) mounting version
Battery pack type:	1 x 12.6 V, 3200 mAh, 40.32 Wh
Battery pack:	Battery operation up to 9h depending on program used Recharging time 2h
Lamp type:	LED lamp
LED type:	4 x 4 W 4in1 RGBW (homogenous color mix)
Flash rate:	1 - 20 Hz
Cooling:	Passive convection cooling
Control:	Sound to light via microphone; stand-alone; IR remote control
Projection:	Flicker-free
Beam angle:	19°
Beam angle (1/2 peak):	19°
Beam angle (1/10 peak):	39°
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Length: 10 cm Width: 11 cm Height: 12 cm
Weight:	1.25 kg
Noise classification:	Class 0 (no noise at all)
Battery:	1 x button cell CR2025

Scope of delivery:

1 x device
1 x user manual
1 x external mains adapter
1 x remote control