

EUROLITE AKKU Mini IP UP-4 QCL Spot MK2

Mini battery uplight IP65 with RGBW LEDs and IR remote control

Art. No.: 41700616

GTIN: 4026397726787



List price: 153.51 €

incl. 19% VAT.

Features:

- Cordless, flexible and versatile
- Battery operation up to 9h depending on program used
- Integrated automatic charging of the battery and status indicator
- 4 LEDs 4 W 4in1 RGBW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable
- Strobe effect; uplight effect
- Direct color selection for 10 preset colors
- The device is cooled by passive convection cooling
- Control via sound to light via microphone; stand-alone; IR remote control
- Flicker-free
- With a beam angle of 15°
- 4 digit 7-segment LED display
- Suitable for outdoor use IP65
- For application areas such as: Architecture; decoration; wedding/gala/events; mobile djs / entertainer; restaurants, bars and hotels; rental; advertisement/Shop window
- Application possibility: Standing
- Silent operation

Logistic

EAN / GTIN: 4026397726787

Weight: 1,27 kg

Length: 0.16 m

Width: 0.13 m

Height: 0.13 m

Technical specifications:

Power supply: 5V 1600 mA

IP classification: IP65

Protection class: Protection class III

Power connection:	Battery/battery pack Mains input via USB C (W) mounting version
Battery pack type:	1 x lithium ion 11.1 V, 3200 mAh, 35.52 Wh
Battery pack:	Battery operation up to 9h depending on program used Recharging time 5h
Lamp type:	LED lamp
LED type:	4 x 4 W 4in1 RGBW (homogenous color mix)
Flash rate:	1 - 20 Hz
Cooling:	Passive convection cooling
Control:	Sound to light via microphone; stand-alone; IR remote control
Projection:	Flicker-free
Beam angle:	15°
Beam angle (1/2 peak):	15°
Beam angle (1/10 peak):	30°
Housing color:	Black
Display type:	4 digit 7-segment LED display
Dimensions:	Length: 10 cm Width: 11 cm Height: 12 cm
Weight:	1.17 kg
Noise classification:	Class 0 (no noise at all)
Battery:	1 x button cell CR2025

Scope of delivery:

1 x light effect
1 x remote control
1 x USB cable
1 x user manual