

EUROLITE PAR-56 Spot CDM150 sil

Long PAR-56 housing for CDM-T 150 discharge lamps

Art. No.: 42000910

GTIN: 4026397426946



List price: 153.51 €

incl. 19% VAT.

Features:

- Rugged metal housing
- 4 clip-to-hold clamps with spring locks for comfortable opening of the color filter frame
- Protective shield is integrated in the tube
- Control via plug and play
- With a beam angle of 55°
- With mounting bracket
- For PAR 56
- For application areas such as: Trade fair and shop fitting; video and photography; advertisement/Shop window

Logistic

EAN / GTIN: 4026397426946

Weight: 4,50 kg

Length: 0.27 m

Width: 0.28 m

Height: 0.46 m

Technical specifications:

Power supply: 230 V AC, 50 Hz

Power consumption: 210 W

Protection class: Protection class I

Power connection: Fixed power supply cord with safety plug

Cable length: Approx. 0.8 m

Base: G-12

Lamp type: Discharge lamp

Color generation: Via color filter frame (optional)

Control: Plug and play

Beam angle:	55°
Beam angle (1/2 peak):	55°
Housing color:	Silver
Attachment system:	Mounting bracket
Dimensions:	Length: 36 cm Width: 24 cm Height: 32 cm
Weight:	4.00 kg

Scope of delivery:

1 x spotlight
1 x filter frame
1 x user manual