

EUROLITE LED STP-15 QCL Bar

3in1 LED bar with RGBW beam effects, color animations and stroboscope

Art. No.: 42103494

GTIN: 4026397710694



List price: 415.31 €

incl. 19% VAT.

Features:

- 14 LEDs 5 W SMD 3535 4in1 RGBW (homogenous color mix)
- 120 LEDs SMD 5050 3in1 RGB (homogenous color mix)
- 180 LEDs SMD 5730 cold white (CW)
- Color blend stepless; running light adjustable; colors preset; Dimmer electronic; background color adjustable; color animations with two adjustable colors
- Strobe effect
- 7 integrated show programs
- Direct color selection for 38-42 preset colors
- Can be operated in 9; 11; 17; 19 CH mode
- The device is cooled by passive convection cooling
- Control via stand-alone; sound to light via microphone; master/slave function; DMX
- Flicker-free
- With a beam angle of 10° beam
- With mounting bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- Built with SEETRONIC connector
- For application areas such as: Clubs/dancing school; wedding/gala/events; stage; mobile djs / entertainer; party room; restaurants, bars and hotels
- Silent operation
- Application possibility: Suspended; wall mounting

Logistic

EAN / GTIN: 4026397710694

Weight: 4,48 kg

Length: 1.05 m

Width: 0.12 m

Height: 0.16 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	120 W
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (grey), mounting version
Lamp type:	LED lamp
LED type:	14 x 5 W SMD 3535 4in1 RGBW (homogenous color mix) 120 x SMD 5050 3in1 RGB (homogenous color mix) 180 x SMD 5730 cold white (CW)
Flash rate:	0 - 20 Hz
DMX channels:	9; 11; 17; 19
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; sound to light via microphone; master/slave function; DMX
Fixtures available for:	Light Captain; Colorchief
Projection:	Flicker-free
Beam angle:	10° beam
Beam angle (1/2 peak):	Beam 10° Ambient light 120°
Beam angle (1/10 peak):	Beam 20°
Housing color:	Black
Attachment system:	2x mounting bracket
Display type:	4 digit 7-segment LED display
Use of brands:	Built with SEETRONIC connector
Dimensions:	Length: 100.0 cm Depth: 6.7 cm Height: 12.0 cm
Weight:	3.96 kg
Noise classification:	Class 0 (no noise at all)

Scope of delivery:

1 x light effect
1 x user manual
1 x power cord