EUROLITE M-200 Mobile TwinTop Light Set

Compact, mobile lighting system

Art. No.: 42109504

GTIN:











Features:

- Combines four LED spots and four Matrix effects
- The standard light system for every small band, solo entertainers and parties
- Set consisting of: 42109700 EUROLITE LED KLS-200 Compact lightset, 51918559 EUROLITE LED MAT-Bar 4x64 Matrix strip, 60004120 Speaker system stand alu, black, 59007081 EUROLITE STV-3529 Adapter long
- Details to the products:
- KLS-200 Compact lightset
- DMX LED spotlight set with 4 spots
- 108 x 10 mm LED per spot (36 x red, 36 x green, 36 x blue)
- Movable and tiltable spotlights
- Sound-control via built-in microhone with sensitivity control
- MAT-Bar 4x64 Matrix strip
- Space-saving solution
- Diverse mounting options; via mounting hole for example
- 256 LEDs
- You can find more information under the respective article
- Control via stand-alone; DMX
- <p>EUROLITE LED KLS-200 Compact-Light-Set
  Bar with 4 spots with 108 LEDs (RGB) each and carrying bag
- Complete LED light set with four slimline LED spots
- Crossbar with integrated DMX control unit
- Installation via TV pin for tripods with 28 mm interior diameter
- Ultra-light ideally suited for mobile use
- Comes pre-assembled with practical transport bag
- 108 x 10 mm LED per spot (36 x red, 36 x green, 36 x blue)
- Movable and tiltable spotlights

Logistic

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

- DMX-controlled operation or stand-alone operation with processor-controlled color change
- Master/Slave operation
- Sound-control via built-in microhone with sensitivity control
- Convenient control possible via optional 4-pedal foot pedal FP-1 (preset, sound control, freeze, blackout)
- DMX512 control via regular DMX controller (occupies 15 channels)
- Optimized for control with the optional control panel DMX LED Operator 4
- Via DMX, each spot can be individually controlled
- DMX functions: dimmer, automatic mode, music control, strobe effect
- Addressing and setting via control panel with 4-digit LED display
- Suited for installation on a lighting stand (not included)
- Ideal for bands, stages or solo entertainers
- Ready for connection with power cord and safety plug
- 432 LEDs 10 mm R/G/B
 spots controlled separately
- Can be operated in 15 CH mode
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; foot switch (optional)
- With a beam angle of 25°
- For further information about this product, please refer to the Data Sheet under "Downloads"
- <p>EUROLITE LED MAT-Bar 4x64 Matrix bar
  Flower effect bar with 256 LEDs (RGB)
- DMX512 control via regular DMX controller (occupies 7 channels)
- The colorful flower beams change their direction of movement at every bass beat in sound controlled mode
- Sound controlled via built-in microphone
- Microphone sensitivity adjustable via rotary control
- Auto mode, speed adjustable via DMX
- Internal programs
- Master/Slave function
- Control panel with 4 buttons and LED display
- Rugged compact housing
- Ready for connection with power cord and plug
- Including mounting bracket and mounting hole (36 mm) with fixation screw for installation on a truss system or stand, and carry bag
- Control via stand-alone; DMX
- <p>OMNITRONIC Speaker System Stand alu bk
  High-quality speaker stand
- Stable speaker stand for mobile use
- The telescopic tube is additionally fixed with a safety pin
- Adjustable height
- <p>EUROLITE STV-3529 Adapter long
  Massive adapter for 35 mm tube, 28 mm TV spigot, maximum load WLL 100 kg
- For stands with telescopic tube 35 mm
- Connection element for cross beam with 28 mm TV spigot
- With M6 and M8 fixation screw
- Heavy version for highest stability
- TV spigot

Technical specifications:

Lamp type:	LED lamp
Control:	Stand-alone; DMX
Housing color:	Black

EUROLITE LED KLS-200 Compact-Light-Set

Power supply:	230 V AC, 50 Hz
Power consumption:	55 W

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Lamp type:	LED lamp
LED type:	432 x 10 mm R/G/B
DMX channels:	15
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; foot switch (optional)
Fixtures available for:	Light´J; LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3
Beam angle:	25°
Beam angle (1/2 peak):	25°
Housing color:	Black
Weight:	8.65 kg
Dimensions:	Width: 120 cm Depth: 12 cm Height: 38 cm
DMX connection:	3-pin XLR
TV spigot:	D = 28 mm
Dimensions (L x W x H):	1110 x 55 x 295 mm

EUROLITE LED MAT-Bar 4x64 Matrix bar

Power supply:	230 V AC, 50 Hz
Power consumption:	40.00 W
Lamp type:	LED lamp
Control:	Stand-alone; DMX
Fixtures available for:	Light´J
Beam angle (1/2 peak):	15°
Housing color:	Black
Dimensions:	Width: 80 cm Depth: 9 cm Height: 23 cm
Weight:	6.48 kg
DMX channels:	7
DMX connection:	3-pin XLR
Sound-control:	via built-in microphone
LED type:	5 mm
LED number:	256
Beam angle:	15°
Mounting hole:	D = 36 mm
Dimensions (L x W x H):	800 x 90 x 230 mm

OMNITRONIC Speaker System Stand alu bk

Maximum carrying capacity:	30 kg

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Height:	Maximum: 230 cm Minimum: 140 cm
Type (general stands):	Speaker stand/manual
Material:	Aluminum
Color:	Black
Weight:	3.45 kg
Maximum load:	30 kg
Maximum load (DIN15560):	18 kg
Minimum height:	1.40 m
Maximum height:	2.20 m

EUROLITE STV-3529 Adapter long

Maximum load BGV C1 (8-fold):	50 kg
Maximum load WLL (4-fold):	100 kg
Attachment system:	TV spigot Ø 28mm Ø 35mm
Type (general stands):	Accessory
Material:	Steel, 6 mm, powder-coated
Dimensions:	Width: 8.50 cm Depth: 5 cm Height: 19.50 cm
Weight:	1.50 kg

Scope of delivery:

1 x EUROLITE LED KLS-200 Compact-Light-Set

1 x spotlight
1 x bag

1 x EUROLITE STV-3529 Adapter long

1 x device
1 x user manual
2 x knurled screw

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.