

EUROLITE KLS-Kombo Pack 6

High performance mobile lighting system

Art. No.: 42109546

GTIN:



The article is no longer in our assortment.

Features:

- Combines four 3-W-LED spots and four LED bars
- The standard light system for every small band, solo entertainers and parties
- Set consisting of: 42109851 EUROLITE LED KLS-801 Compact lightset, 2 x 42109928 EUROLITE LED ACS BAR-12 6000K 12x1W, 2 x 42109929 EUROLITE LED ACS BAR-12 3200K 12x1W, 60004120 Speaker system stand alu, black, 59007081 EUROLITE STV-3529 Adapter long
- Details to the products:
- KLS-801 Compact lightset
- Complete LED light set with 4 spots
- Compact and easy to transport
- 28 3-W-TCL LEDs
- 4 IEC outputs for power supply of further devices
- ACS BAR-12 12x1W
- Equipped with 12 x 1 W LEDs
- Beam angle approximately 16°
- Floor, ceiling or trussing installation possible
- LED intensity and strobe settings
- You can find more information under the respective article
- **Bar with 4 spots with 7 x 3 W 3in1 LED (RGB) each and carrying bag**
- Complete LED light set with four slimline LED spots
- Crossbar with integrated DMX control unit
- Installation via TV pin for tripods with 28 mm interior diameter
- Ultra-light ideally suited for mobile use
- Comes pre-assembled with practical transport bag
- 7 TCL LEDs per spot

Logistic

- Through the close chip placement of the multichip technology, an exquisite color mix even with short distances to the illuminated surface is provided
- Movable and tiltable spotlights
- DMX-controlled operation or stand-alone operation with processor-controlled color change
- Master/Slave operation
- Sound-control via built-in microphone with sensitivity control
- Convenient control possible via optional 4-pedal foot pedal FP-1 or IR remote control
- Optimized for control with the optional control panel DMX LED Operator 4
- Via DMX, each spot can be individually controlled
- DMX functions: dimmer, automatic mode, music control, strobe effect
- Addressing and setting via control panel with 4-digit LED display
- Suited for installation on a lighting stand (not included) or truss
- Black lacquered metal version
- Ideal for bands, stages or solo entertainers
- Ready for connection with power cord and safety plug
- 4 IEC outputs for power supply of further devices
- 7 LEDs 3 W high-power 3in1 RGB (homogenous color mix)
 spots controlled separately
- Can be operated in 15 CH mode
- Control via stand-alone; DMX; foot switch (optional); sound to light via microphone
- With a beam angle of 30°
- TV spigot
- For further information about this product, please refer to the Data Sheet under "Downloads"
- <p>OMNITRONIC Speaker System Stand alu bk

High-quality speaker stand

- Stable speaker stand for mobile use
- The telescopic tube is additionally fixed with a safety pin
- Adjustable height
- <p>EUROLITE STV-3529 Adapter long

Massive adapter for 35 mm tube, 28 mm TV spigot, maximum load WLL 100 kg

- For stands with telescopic tube 35 mm
- Connection element for cross beam with 28 mm TV spigot
- With M6 and M8 fixation screw
- Heavy version for highest stability
- TV spigot
- <p>EUROLITE LED ACS BAR-12 6000K 12x1W

Handy professional light bar with cold white LEDs

- Equipped with 12 x 1 W LEDs
- Beam angle approximately 16°
- Floor, ceiling or trussing installation possible
- Locking possibility at the mounting bracket
- Operable in stand-alone mode or via DMX
- 2 or 5 DMX channels selectable for numerous applications
- Sound-control via built-in microphone
- Adjustable microphone sensitivity via control panel
- Comfortable addressing and setting via control panel with LED screen and three operating buttons
- Functions: LED intensity and strobe settings via DMX, Master/Slave
- Ready for connection via power cord with IEC plug for direct KLS-connection
- For stand alone operation you need a normal power cord with safety plug
- 12 LEDs 1 W high-power cold white (CW)
- Can be operated in 2; 5 CH mode
- Control via stand-alone; DMX; sound to light via microphone
- With a beam angle of 16°
- <p>EUROLITE LED ACS BAR-12 3200K 12x1W

Handy professional light bar with warm white LEDs

- Equipped with 12 x 1 W LEDs
- Beam angle approximately 16°
- Floor, ceiling or trussing installation possible
- Locking possibility at the mounting bracket
- Operable in stand-alone mode or via DMX
- 2 or 5 DMX channels selectable for numerous applications
- Sound-control via built-in microphone
- Adjustable microphone sensitivity via control panel
- Comfortable addressing and setting via control panel with LED screen and three operating buttons
- Functions: LED intensity and strobe settings via DMX, Master/Slave

- Ready for connection via power cord with IEC plug for direct KLS-connection
- For stand alone operation you need a normal power cord with safety plug
- <p>OMNITRONIC XLR Cable 3-pin 0.5m bk

Audio cable with 3-pin XLR connectors

Technical specifications:

Weight:	22.70 kg
---------	----------

EUROLITE LED KLS-801 Compact Light Set

Power supply:	230 V AC, 50 Hz
Power consumption:	90.00 W
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	4 x IEC connector (F) mounting version fused 1 x IEC connector (F) mounting version Bypass
Lamp type:	LED lamp
LED type:	7 x 3 W high-power 3in1 RGB (homogenous color mix)
DMX channels:	15
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Control:	Stand-alone; DMX; foot switch (optional); sound to light via microphone
Fixtures available for:	Light´ J; LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3
Beam angle:	30°
Beam angle (1/2 peak):	30°
Housing color:	Black
Attachment system:	TV spigot Ø 28mm
Weight:	11.75 kg
Dimensions:	Width: 120 cm Depth: 6.5 cm Height: 31.5 cm
Dimensions:	Width: 125 cm Depth: 12 cm Height: 38 cm

OMNITRONIC Speaker System Stand alu bk

Maximum carrying capacity:	30 kg
Height:	Maximum: 230 cm Minimum: 140 cm
Type (general stands):	Speaker stand/manual
Material:	Aluminum

Color:	Black
Weight:	3.45 kg
Maximum load:	30 kg
Maximum load (DIN15560):	18 kg
Minimum height:	1.40 m
Maximum height:	2.20 m

EUROLITE STV-3529 Adapter long

Maximum load BGV C1 (8-fold):	50 kg
Maximum load WLL (4-fold):	100 kg
Attachment system:	TV spigot Ø 28mm Ø 35mm
Type (general stands):	Accessory
Material:	Steel, 6 mm, powder-coated
Dimensions:	Width: 8.50 cm Depth: 5 cm Height: 19.50 cm
Weight:	1.50 kg

EUROLITE LED ACS BAR-12 6000K 12x1W

Power supply:	230 V AC, 50 Hz
Power consumption:	20.00 W
Power connection:	Fixed power supply cord with safety plug
Lamp type:	LED lamp
LED type:	12 x 1 W high-power cold white (CW)
DMX channels:	2; 5
Control:	Stand-alone; DMX; sound to light via microphone
Fixtures available for:	Light´J
Beam angle:	16°
Beam angle (1/2 peak):	16°
Housing color:	Black
Dimensions:	Width: 28.5 cm Depth: 8 cm Height: 13 cm
Weight:	1.49 kg
DMX connection:	3-pin XLR

EUROLITE LED ACS BAR-12 3200K 12x1W

Power supply:	230 V AC, 50 Hz
Power consumption:	20.00 W
Fixtures available for:	Light´J
Dimensions:	Width: 28.5 cm

	Depth: 8 cm
	Height: 13 cm
Weight:	1.47 kg
DMX channels:	2/5
DMX connection:	3-pin XLR
Sound-control:	via built-in microphone
LED type:	1 W
LED number:	12
Beam angle:	16°
Dimensions (L x W x H):	80 x 285 x 130 mm

OMNITRONIC XLR Cable 3-pin 0.5m bk

Cable construction:	Audio cable
Cable length:	0.5 m
Plug A:	1 x 3-pin XLR (M)
Plug B:	1 x 3-pin XLR (F)
Color:	Black
Weight:	0.08 kg

Scope of delivery:

1 x EUROLITE LED KLS-801 Compact Light Set

1 x spotlight
1 x bag

1 x EUROLITE STV-3529 Adapter long

1 x device
1 x user manual
2 x knurled screw

1 x OMNITRONIC XLR Cable 3-pin 0.5m bk

1 x XLR cable