

EUROLITE LED KLS-120 FX Compact Light Set

DMX lighting effect bar with 2 rotating LED derbies and 2 LED spotlights

Art. No.: 42109607

GTIN: 4026397680751



Features:

- Crossbar with integrated DMX control unit and stand sleeve
- Compact lightweight
- 2 rotating derbies for mirror ball effects
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- 3 integrated show programs
- Direct color selection for 15 preset colors
- Can be operated in 2; 9; 21 CH mode
- The device is cooled by passive convection cooling
- Control via DMX; IR remote control; stand-alone; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- With a beam angle of 18° wash effect
- 4 digit 7-segment LED display
- 6 x rubber feet
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; decoration; mobile djs / entertainer; party room; restaurants, bars and hotels
- Silent operation
- Application possibility: Standing; on stand
- spotlight**
- 3 LEDs 8 W COB (chip-on-board) 4in1 RGBW (homogenous color mix)
 spots controlled separately
- light effect**
- 4 LEDs 3 W SMD 9080 R/G/B/W
 LEDs controlled separately

Logistic

EAN / GTIN: 4026397680751

Weight: 5,40 kg

Length: 0.66 m

Width: 0.17 m

Heigh: 0.36 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	45 W
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug included
Power output:	IEC connector (F) mounting version
Fuse:	T 1 A fuse replaceable
Lamp type:	LED lamp
Flash rate:	0.5 - 20 Hz
DMX channels:	2; 9; 21
DMX input:	3-pin XLR (F) mounting version
DMX output:	3-pin XLR (M) mounting version
Cooling:	Passive convection cooling
Control:	DMX; IR remote control; stand-alone; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	Light Captain; EASY SHOW 2; EASY SHOW 3; Light´J; Colorchief
Projection:	Flicker-free
PWM frequency:	2900 Hz
Beam angle:	18° wash effect
Beam angle (1/2 peak):	Wash effect 18° Multi beam effect 90° multicolor
Housing color:	Black
Attachment system:	Tube: 1x Ø 35mm
Display type:	4 digit 7-segment LED display
Transport aid:	6 x rubber feet
Dimensions:	Width: 62.5 cm Depth: 15.5 cm Height: 22.4 cm
Weight:	4.70 kg
Noise classification:	Class 0 (no noise at all)
LED type:	4 x 3 W SMD 9080 R/G/B/W
Cable construction:	H05VV-F
Cable length:	Approx. 1.2 m
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
LED type:	3 x 8 W COB (chip-on-board) 4in1 RGBW (homogenous color mix)

Scope of delivery:

1 x light effect
1 x power cord
1 x remote control
1 x battery
1 x bag
1 x user manual