

## EUROLITE LED KLS-120 Laser FX II Compact Light Set

DMX light effect bar with 2 rotating LED derbies, 2 LED spots and 2 lasers (RG/2M)

Art. No.: 42109650

GTIN: 4026397689358



### Features:

- Crossbar with integrated DMX control unit and stand sleeve
- 2 laser diodes project hundreds of red and green laser beams
- 2 rotating derbies for mirror ball effects
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- 7 integrated show programs
- Direct color selection for 15 preset colors
- Can be operated in 3; 13; 25 CH mode
- The device is cooled by passive convection cooling
- Control via DMX; IR remote control; stand-alone; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- 4 digit 7-segment LED display
- Rubber feet
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; decoration; mobile djs / entertainer; party room; restaurants, bars and hotels
- Application possibility: On stand; suspended
- Silent operation
- laser**
- Laser class 2M <BR> does not require additional protective measures or appointment of a laser safety officer
- spotlight**
- 3 LEDs 8 W COB (chip-on-board) 4in1 RGBW (homogenous color mix)<BR> spots controlled separately

### Logistic

EAN / GTIN: 4026397689358

Weight: 5,80 kg

Length: 0.67 m

Width: 0.17 m

Height: 0.35 m

- With a beam angle of 18°  
**light effect**
- 4 LEDs 3 W SMD 8072 R/G/B/W<BR> spots controlled separately

## Technical specifications:

|                         |                                                                                                                                                                                                              |
|-------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power supply:           | 100-240 V AC, 50/60 Hz                                                                                                                                                                                       |
| Power consumption:      | 40 W                                                                                                                                                                                                         |
| Protection class:       | Protection class I                                                                                                                                                                                           |
| Power connection:       | Mains input via IEC connector (M) mounting version power supply cord with safety plug                                                                                                                        |
| Power output:           | IEC connector (F) mounting version                                                                                                                                                                           |
| Fuse:                   | 5 x 20 mm, T 1 A fuse replaceable                                                                                                                                                                            |
| Lamp type:              | LED lamp                                                                                                                                                                                                     |
| DMX channels:           | 3; 13; 25                                                                                                                                                                                                    |
| DMX input:              | 3-pin XLR (M) mounting version                                                                                                                                                                               |
| DMX output:             | 3-pin XLR (F) mounting version                                                                                                                                                                               |
| Cooling:                | Passive convection cooling                                                                                                                                                                                   |
| Control:                | DMX; IR remote control; stand-alone; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) |
| Fixtures available for: | Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief                                                                                                                                                          |
| Projection:             | Flicker-free                                                                                                                                                                                                 |
| Housing color:          | Black                                                                                                                                                                                                        |
| Attachment system:      | Tube: 1x Ø 35mm                                                                                                                                                                                              |
| Display type:           | 4 digit 7-segment LED display                                                                                                                                                                                |
| Transport aid:          | Rubber feet                                                                                                                                                                                                  |
| Dimensions:             | Width: 62.5 cm<br>Depth: 15.5 cm<br>Height: 22.9 cm                                                                                                                                                          |
| Weight:                 | 4.60 kg                                                                                                                                                                                                      |
| Noise classification:   | Class 0 (no noise at all)                                                                                                                                                                                    |
| Battery:                | 1 x button cell 3.0 V CR2025 lithium manganese built-in                                                                                                                                                      |
| LED type:               | 3 x 8 W COB (chip-on-board) 4in1 RGBW (homogenous color mix)                                                                                                                                                 |
| Beam angle:             | 18°                                                                                                                                                                                                          |
| Beam angle (1/2 peak):  | 18°                                                                                                                                                                                                          |
| Beam angle (1/10 peak): | 34                                                                                                                                                                                                           |
| LED type:               | 4 x 3 W SMD 8072 R/G/B/W                                                                                                                                                                                     |
| Laser class:            | 2M                                                                                                                                                                                                           |
| Laser color:            | R/G                                                                                                                                                                                                          |
| Laser module:           | Green (G) 14 mW<br>Red (R) 40 mW                                                                                                                                                                             |

## Scope of delivery:

---

1 x device  
1 x user manual  
1 x power cord  
1 x remote control  
1 x battery  
1 x bag