

EUROLITE LED KLS-801 Compact Light Set

Bar with 4 spots with 7 x 3 W 3in1 LED (RGB) each and carrying bag

Art. No.: 42109851

GTIN: 4026397420272



The article is no longer in our assortment.

Features:

- Complete LED light set with four slimline LED spots
- Crossbar with integrated DMX control unit
- Installation via TV pin for tripods with 28 mm interior diameter
- Ultra-light ideally suited for mobile use
- Comes pre-assembled with practical transport bag
- 7 TCL LEDs per spot
- Through the close chip placement of the multichip technology, an exquisite color mix even with short distances to the illuminated surface is provided
- Movable and tiltable spotlights
- DMX-controlled operation or stand-alone operation with processor-controlled color change
- Master/Slave operation
- Sound-control via built-in microphone with sensitivity control
- Convenient control possible via optional 4-pedal foot pedal FP-1 or IR remote control
- Optimized for control with the optional control panel DMX LED Operator 4
- Via DMX, each spot can be individually controlled
- DMX functions: dimmer, automatic mode, music control, strobe effect
- Addressing and setting via control panel with 4-digit LED display
- Suited for installation on a lighting stand (not included) or truss
- Black lacquered metal version
- Ideal for bands, stages or solo entertainers
- Ready for connection with power cord and safety plug
- 4 IEC outputs for power supply of further devices
- 7 LEDs 3 W high-power 3in1 RGB (homogenous color mix)
 spots controlled separately
- Can be operated in 15 CH mode
- Control via stand-alone; DMX; foot switch (optional); sound to light via microphone
- With a beam angle of 30°

Logistic

EAN / GTIN: 4026397420272

Weight: 13,10 kg

Length: 1.26 m

Width: 0.13 m

Height: 0.40 m

Bulky product

- TV spigot
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	90.00 W
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	4 x IEC connector (F) mounting version fused 1 x IEC connector (F) mounting version Bypass
Lamp type:	LED lamp
LED type:	7 x 3 W high-power 3in1 RGB (homogenous color mix)
DMX channels:	15
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Control:	Stand-alone; DMX; foot switch (optional); sound to light via microphone
Fixtures available for:	Light´J; LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3
Beam angle:	30°
Beam angle (1/2 peak):	30°
Housing color:	Black
Attachment system:	TV spigot Ø 28mm
Weight:	11.75 kg
Dimensions:	Width: 120 cm Depth: 6.5 cm Height: 31.5 cm
Dimensions:	Width: 125 cm Depth: 12 cm Height: 38 cm

Scope of delivery:

1 x spotlight
1 x bag