

EUROLITE LED KLS-2500 Compact-Light-Set

Bar with 4 spots with 7 x 10 W 5in1 LED each, with 5-pin QuickDMX connector

Art. No.: 42109892

GTIN: 4026397517163



Features:

- Complete LED light set with four slimline LED spots
- Crossbar with integrated DMX control unit
- Installation via TV pin for tripods with 28 mm interior diameter
- Ultra-light ideally suited for mobile use
- 7 PCL LEDs (RGBAW) per spot
- Comes pre-assembled with practical transport bag
- Movable and tiltable spotlights
- Sound-control via built-in microphone with sensitivity control
- DMX-controlled operation or stand-alone operation with processor-controlled color change
- Supports QuickDMX - the wireless DMX-system from Eurolite
- Built-in phantom fed socket for QuickDMX receiver (see accessories)
- Master/Slave operation
- Sound-control via built-in microphone with sensitivity control
- Convenient control possible via optional foot pedal FP-1
- DMX512 control via regular DMX controller (occupies 28 channels)
- Via DMX, each spot can be individually controlled
- DMX functions: dimmer, automatic mode, music control, strobe effect
- Addressing and setting via control panel with OLED display
- Suited for installation on a lighting stand (not included) or truss
- Black lacquered metal version
- Ideal for bands, stages or solo entertainers
- Ready for connection with power cord and PowerCon input
- 4 IEC outputs for power supply of further devices
- 7 LEDs 10 W high-power 5in1 RGBWA (homogenous color mix)
 spots controlled separately
- Can be operated in 2; 3; 4; 7; 20; 23; 28 CH mode

Logistic

EAN / GTIN: 4026397517163

Weight: 16,70 kg

Length: 1.26 m

Width: 0.13 m

Height: 0.40 m

Bulky product

- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; foot switch (optional)
- With a beam angle of 17°

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	190.00 W
Power connection:	Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x PowerCON (grey), mounting version
Lamp type:	LED lamp
LED type:	7 x 10 W high-power 5in1 RGBWA (homogenous color mix)
DMX channels:	2; 3; 4; 7; 20; 23; 28
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; foot switch (optional)
Fixtures available for:	Light´J; LED PC-Control 512; EASY SHOW 1; Light Captain
Beam angle:	17°
Beam angle (1/2 peak):	17°
Beam angle (1/10 peak):	30°
Housing color:	Black
Dimensions:	Width: 120 cm Depth: 6 cm Height: 32 cm
Weight:	15.70 kg
DMX channels:	2/3/4/7/20/23/28
DMX connection:	3-pin XLR
QuickDMX connection:	5-pin XLR
Sound-control:	via built-in microphone
LED type:	10 W RGBAW (5in1)
Number of LEDs:	28
Beam angle:	28°
TV spigot:	D = 28 mm
Dimensions (L x W x H):	1160 x 60 x 320 mm

Scope of delivery:

1 x spotlight