

EUROLITE LED PARTY TCL Spot

Compact spotlight with 12 x 3 W 3in1 RGB LED and DMX control

Art. No.: 42110193

GTIN: 4026397672640



Description:

Only 0.5 kg light and easily portable with one finger - the LED PARTY TCL spot is one of the smallest and lightest entertainers among the PAR spots!

Twelve high-performance RGB LEDs produce thrilling color mixtures, rapid color changes, dimmed light as well as dynamic strobe effects. The fixture can be controlled via DMX or operated in standalone mode. Color change, dimmer and strobe are adjustable - and of course, there's also a sound control mode.

Thanks to the integrated mounting bracket, the spot can be easily installed even by laymen. What is more, the modern LED technology makes it particularly energy-efficient.

All in all, the LED PARTY is perfectly suited for home use - for parties at home as well as for kids' rooms. Just put the plug into the socket and get the party started!

Features:

- 12 LEDs 3 W SMD 8072 3in1 RGB (homogenous color mix)
- Color change programs; color blend stepless; pulse effect adjustable; Dimmer electronic
- Strobe effect
- Direct color selection for 18 preset colors
- Can be operated in 5 CH mode
- The device is cooled by cooling fan
- Control via stand-alone; DMX; sound to light via microphone
- Flicker-free
- With a beam angle of 17°
- With mounting bracket
- 4 digit 7-segment LED display

Logistic

EAN / GTIN: 4026397672640

Weight: 0,50 kg

Length: 0.15 m

Width: 0.13 m

Height: 0.12 m

- For application areas such as: Decoration; mobile djs / entertainer; party room
- Application possibility: Suspended; on stand

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	10 W
Protection class:	Protection class II
Power connection:	Fixed power supply cord with Euro plug
Cable construction:	2 x 0.75 mm² H03VVH2-F
Lamp type:	LED lamp
LED type:	12 x 3 W SMD 8072 3in1 RGB (homogenous color mix)
Flash rate:	0.5 - 16 Hz
DMX channels:	5
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	1 x cooling fan
Control:	Stand-alone; DMX; sound to light via microphone
Fixtures available for:	LED PC-Control 512; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; Light´J; Colorchief
Projection:	Flicker-free
PWM frequency:	15700 Hz
Beam angle:	17°
Beam angle (1/2 peak):	17°
Beam angle (1/10 peak):	38°
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Width: 15 cm Depth: 9 cm Height: 16 cm
Weight:	0.43 kg
Noise classification:	Class 2 (slight noise)
Diameter mounting holes:	1 x Ø12mm; 2 x Ø8mm
Material:	Metal, 1 mm, painted

Scope of delivery:

- 1 x light effect
- 1 x mounting bracket
- 2 x knurled screw
- 2 x washer
- 1 x user manual