

EUROLITE LED Umbrella 140

Extraordinary RGB eye-catcher

Art. No.: 42111000

GTIN: 4026397625684



The article is no longer in our assortment.

Features:

- DMX-controllable lighting effect umbrella with 114 SMD RGB LEDs, distributed in 7 segments
- Segments can be controlled individually via DMX
- 6 segments make the surface of the umbrella shine, one segment in the middle shines directly at the audience
- Perfect as stage background and eye-catcher for decorative purposes in shops, display windows, fair stands, hotels, bars and clubs
- Can be mounted to a lighting stand or trussing - the umbrella's angle can be adjusted
- Easy transport (can be folded), setup and installation
- Covers a large area with a diameter of 140 cm
- Built-in auto and music show programs
- Supports QuickDMX - the wireless DMX-system from Eurolite
- Built-in phantom-powered USB port for QuickDMX receivers (accessories)
- Stepless RGB color mixture, dimmer and strobe effect
- Addressing via control panel with 4-digit LED display
- Appropriate control unit included in the delivery
- Power connection via P-Con jack and included power cable with safety plug
- 114 LEDs SMD 5050 3in1 RGB (homogenous color mix)
- Can be operated in 6; 24 CH mode
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free

Logistic

EAN / GTIN: 4026397625684

Weight: 4,75 kg

Length: 1.02 m

Width: 0.29 m

Height: 0.29 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	20 W
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Lamp type:	LED lamp
LED type:	114 x SMD 5050 3in1 RGB (homogenous color mix)
DMX channels:	6; 24
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	Light´ J; LED PC-Control 512; Light Captain
Projection:	Flicker-free
Dimensions:	Diameter: Ø 140 cm
Weight:	3.07 kg

Scope of delivery:

1 x omega bracket
1 x device
1 x user manual
1 x power cord
1 x multipin cable
1 x umbrella